



Memorandum

October 7, 2016

To: Mr. Richard Conforti/MDEQ Ref. No.: 012636

From: Michael Tomka/kf/91 

CC: Joe Rogers, John McCabe/MDEQ
Dave Favero/RACER, Clifford Yantz/OBG

Subject: PFOS/PFAS Sampling at RACER Former Peregrine, Inc., Coldwater Road Facility (MIR 000 020 743) and Coldwater Road Landfill (MID 005 356 860), Genesee Township, Michigan

1. Introduction

In response to comment 3 from the Michigan Department of Environmental Quality (MDEQ) dated July 13, 2016, and subsequent email correspondence, RACER is proceeding with sampling groundwater at select locations at the Former Peregrine, Inc., Coldwater Road Facility and the Coldwater Road Landfill for Perfluorinated chemicals (PFCs), including Perfluorooctanoic Acid (PFOA) and Perfluorooctane Sulfonate (PFOS) analysis.

2. Locations

Groundwater samples will be collected from the Former Peregrine, Inc., Coldwater Road Facility and the Coldwater Road Landfill. The following locations (monitoring wells and sump) will be sampled:

1. Coldwater Road Landfill
 - a. Monitoring wells - B-7, B-19AR
 - b. Sump D
2. Former Peregrine, Inc., Coldwater Road Facility
 - a. Monitoring wells - MW-4-02, MW-16-10, MW-18-13, MW-19-13

Attachment A presents figures identifying the proposed sample locations.

3. Procedures

Shallow groundwater samples will be collected using standard low flow procedures. Deep groundwater samples will be collected using standard volumetric purging procedures. Peristaltic (for shallow wells) and/or stainless steel inertial (for deep wells) pumps will be used for purging. Only new HDPE and silicon tubing will



be used in the sampling process. The pumps utilized for the PFC sampling will not contain Teflon, LDPE, or Viton components. Details of the sample procedures are presented in Attachment B (OBG Procedures) and Attachment C (GHD Procedures). The sampling procedures are intended to prevent cross contamination of samples by PFCs. The sample crews will work together to ensure that all samples are collect consistent with these procedures.

In addition, due to the sensitivity of the PFC analysis, the checklist in Attachment D will be utilized.

4. Analysis

Samples will be analyzed for PFCs by TestAmerica Laboratories, Inc. in Sacramento, California using Modified Method 537. The list of analytes and reporting limits are presented on Table 1.

Quality Assurance/Quality Control (QA/QC) samples will be collected and will include 1 duplicate, 1 field blank, 1 matrix spike/matrix spike duplicate, 1 equipment blank and 1 trip blank.

TestAmerica will provide level IV data packages. Data validation will be performed by GHD and OBG for the samples collected at the Former Peregrine Facility and Landfill, respectively.

5. Schedule

The sampling will be completed the week of November 28, 2016. Representatives from both OBG and GHD will be present and sampling will be completed as a joint activity to ensure continuity of the event.

6. Reporting

Following receipt and validation of the samples, technical memorandums will be prepared for each site to summarize the sample event and present the sample results. The technical memorandums will be submitted to the MDEQ.

7. Attachments

Table 1	PFC Method, Analytes, and Reporting Limits
Attachment A	Sample Locations
Attachment B	OBG Groundwater Sampling Procedure
Attachment C	GHD Groundwater Sampling Procedure
Attachment D	PFC Sampling Checklist


**PFC Method, Analytes, and Reporting Limits
Coldwater Road Landfill
Genesee Township, Michigan**

Analysis Group	Analyte Description	CAS Number	RL	MDL	Units
PFCs in Water-Sacramento Standard List Modified Method 537	Perfluorobutanoic acid (PFBA)	375-22-4	2.00	0.458	ng/L
	Perfluoropentanoic acid (PFPeA)	2706-90-3	2.00	0.989	ng/L
	Perfluorohexanoic acid (PFHxA)	307-24-4	2.00	0.786	ng/L
	Perfluoroheptanoic acid (PFHpA)	375-85-9	2.00	0.802	ng/L
	Perfluorooctanoic acid (PFOA)	335-67-1	2.00	0.748	ng/L
	Perfluorononanoic acid (PFNA)	375-95-1	2.00	0.654	ng/L
	Perfluorodecanoic acid (PFDA)	335-76-2	2.00	0.440	ng/L
	Perfluoroundecanoic acid (PFUnA)	2058-94-8	2.00	0.748	ng/L
	Perfluorododecanoic acid (PFDoA)	307-55-1	2.00	0.584	ng/L
	Perfluorotridecanoic Acid (PFTriA)	72629-94-8	2.00	0.551	ng/L
	Perfluorotetradecanoic acid (PFTeA)	376-06-7	2.00	0.199	ng/L
	Perfluorobutanesulfonic acid (PFBS)	375-73-5	2.00	0.918	ng/L
	Perfluorohexanesulfonic acid (PFHxS)	355-46-4	2.00	0.870	ng/L
	Perfluoroheptanesulfonic Acid (PFHpS)	375-92-8	2.00	0.713	ng/L
	Perfluorooctanesulfonic acid (PFOS)	1763-23-1	2.00	1.28	ng/L
	Perfluorodecanesulfonic acid (PFDS)	335-77-3	2.00	1.21	ng/L
	Perfluorooctane Sulfonamide (FOSA)	754-91-6	2.00	0.638	ng/L

Attachment A Sample Locations

PLOTDATE: 08/22/11 3:14:42 PM schneikh

I:\Racer-Trust\15388\62658\Coldwater-Rd-LIDocs\Reports\GW Monitoring\Semi-Annual\Figures\002 - Figure 2 GW_Report_Site_Layout (2016-06).mxd




LEGEND

-  LEACHATE COLLECTION SUMP
-  ACCESS PORT FOR LEAK DETECTION VAULT
-  MONITORING WELL
-  ABANDONED WELL

RACER TRUST
COLDWATER ROAD
LANDFILL FACILITY
FLINT, MICHIGAN

SITE LAYOUT



AUGUST 2016
15388/62658/002



O'BRIEN & GERE ENGINEERS, INC.

Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AEX, Getmapping, Aerogrid, IGN, IGP, swisstopo, and the GIS User Community

LEGEND

-  FACILITY BOUNDARY
-  SHALLOW MONITORING WELL LOCATION (ANNUAL)
-  DEEP MONITORING WELL LOCATION (ANNUAL)
-  QUARTERLY MONITORING LOCATION
-  STORM SEWER LINE
-  SANITARY SEWER LINE
-  MANHOLE
-  STORM SEWER MONITORING LOCATION

NOTE:
 (1) LOCATION PURGED TO DRY AND SAMPLED FOLLOWING SUFFICIENT RECHARGE. ALL OTHER LOCATIONS SAMPLED USING LOW FLOW PROCEDURES.





figure 1

**GROUNDWATER MONITORING LOCATIONS
 FORMER PEREGRINE (US), INC. COLDWATER ROAD FACILITY
 Genesee Township, Michigan**



NOTE:
 THIS DRAWING IS FOR REFERENCE ONLY AND IS NEITHER COMPLETE NOR TO EXACTING SCALE.

Attachment B

OBG Groundwater Sampling Procedures

TABLE OF CONTENTS

1 Introduction	1
2 Procedural Guidelines.....	1
2.1 Preparatory Requirements	1
2.2 Well Purging and Stabilization Monitoring (Low Stress/Low Flow Method)	1
2.3 Sample Preservation.....	2
2.4 Sample Management and Chain-of-Custody.....	3
2.5 Quality Assurance/Quality Control (QA/QC) Measures.....	3
3 References.....	4



1 INTRODUCTION

This procedure is for the collection of groundwater samples for laboratory analysis.

The objective of most groundwater quality monitoring programs is to obtain samples that are representative of existing groundwater conditions, or samples that retain the physical and chemical properties of the groundwater within an aquifer.

One of the most important aspects of groundwater sampling is acquiring samples that are free of suspended silt, sediment, or other fine grained particulates. Fine grain materials may often have a variety of chemical components sorbed to the particle or have the ability to sorb chemicals from the aqueous phase to the particle, which will bias the subsequent analytical results.

Constituents known to have an affinity for fine-grained particulates are: polychlorinated biphenyls (PCBs), semi-volatile organic compounds (SVOCs), and inorganics. Monitoring programs where these constituents are suspected or known to be prevalent must employ sampling methods that minimize particulate presence.

The “Low Stress/Low Flow” purging and sampling method will be utilized to purge the well to allow representative water from the formation to replace the standing water within the sampling zone of the well. Experience has shown that the low stress/low flow technique typically achieves representative groundwater samples with minimal particulate interference.

Lastly, in extreme cases “ultra-low flow” techniques have been employed at select sites where low stress/low flow methods were used, yet particulate-sensitive constituents continue to bias the analytical results, or excessive drawdown is produced using standard low stress/low flow methods due to the presence of low permeability materials within a well’s screened zone. Ultra-low flow techniques are conducted at purging rates below 100 ml per minute, and should only be utilized after low stress/low flow methods have been attempted.



2 PROCEDURAL GUIDELINES

The following describes techniques for groundwater sampling: Low Stress/Low Flow Methods.

Low stress/low flow methods will be employed when it is critical to collect groundwater samples truly representative of the groundwater present, and to minimize the impact of sediment/colloid presence.

2.1 PREPARATORY REQUIREMENTS

Prior to groundwater sampling, an inspection will be performed on each well. The inspection will include:

- Inspecting the concrete pad for cracks
- Inspecting the protective steel cover
- Inspecting the integrity of the PVC well casing (to the extent possible)
- Inspecting the well caps
- Inspecting the well identification markings to confirm they are legible (if illegible, re-mark)
- Inspecting the locks to assess whether they are in good working condition.

Results of the well inspection will be documented on the Groundwater Sampling Log for each well. If the inspection indicates repairs are required, these will be performed prior to the next sampling event. Corrective actions implemented to repair well(s) will also be documented on the Groundwater Sampling Log and/or the field notebook for the facility.

Groundwater purging and sampling data will be recorded on the Groundwater Sampling Log.

2.2 WELL PURGING AND STABILIZATION MONITORING (LOW STRESS/LOW FLOW METHOD)

The procedure for sampling the monitoring wells is as follows:

- 1) Sampling equipment will first be decontaminated prior to each use by the following protocol:
 - Scrub equipment thoroughly in a low-sudsing detergent solution (*e.g.*, Alconox). Pump low-sudsing detergent solution through submersible pump for approximately 5 minutes, if utilized
 - Rinse equipment thoroughly with distilled water, and pump distilled water through submersible pump, if utilized
 - Wrap equipment in plastic for handling and/or storage until next use
 - Decontamination of disposable tubing, if used, will not be necessary
- 2) Calibrate field instrument and document calibration activity. Calibration shall be performed in accordance with manufacturer's recommendations, and noted on the Groundwater Sampling Log
- 3) An electric water level probe will be used to measure the depth from the top of the casing to the top of water to the nearest 0.01-ft. The measurement will be recorded in a dedicated field notebook and Groundwater Sampling Log
- 4) Measure the depth from the top of casing to the bottom of the well for the initial sampling event
- 5) Slowly lower the pump and/or tubing into the well positioning the pump intake at the mid-point of the well screen taking care to minimize disturbing the well
- 6) During the purging of the well, monitor and record the field indicator parameters (pH, temperature, conductivity, oxidation-reduction (redox) reaction potential (ORP), dissolved oxygen (DO), and turbidity) approximately every 5 minutes. Stabilization is considered achieved when the final groundwater flow rate is achieved, and three consecutive readings for each parameter are within the following limits:

pH	±0.1 pH units for three consecutive readings;
temperature	±3 percent for three consecutive readings;
conductivity	±3 percent for three consecutive readings;
ORP	±10 millivolts (mV) for three consecutive readings;
DO	±10 percent for three consecutive readings; and
Turbidity	±10 percent for three consecutive readings or a final value of less than 5 nephelometric turbidity units (NTU).

- 7) Verify that drawdowns of 0.3 ft or less are maintained and make adjustments as necessary. Record drawdown measurements and note adjustments in pumping rates as necessary on the Groundwater Sampling Log. If drawdowns of 0.3 ft or less cannot be maintained utilize ultra-low flow purge techniques. However, if ultra-low flow purging still results in the well purging “dry,” allow the well to recharge and the sample will be collected as soon as sufficient water is present to obtain the necessary sample volume
- 8) Obtain a sample for chemical analyses immediately upon stabilization of field parameter measurements. Field filter the sample for dissolved metals using a 0.45-micron filter prior to preserving with acid. Samples are to be collected in the order of volatility as follows: TOC/TOX (or VOCs) and dissolved metals.

If after 2 hours of purging the indicator parameters have not stabilized, as recommended in the USEPA guidance, the purging will be discontinued and the sample will be collected with an explanation of attempts to achieve stabilization.

Either a decontaminated submersible pump or peristaltic pump (for shallow wells only) may be utilized to purge each well. If a submersible pump is utilized in the purging process, then it will be decontaminated prior to and after sampling each well. Sampling equipment must be protected from the ground surface by a clean plastic sheet laid around the work area. Water from purging will not be containerized.

2.3 SAMPLE PRESERVATION

Sample bottles will be labeled with sample identification, collection date and time, filtration/preservative status. Sample bottles will be filled and capped securely and immediately preserved (if required) and stored at 4 degrees Celsius in a cooler.

The cooler and samples will be prepared for shipment or transport by the following procedure:

- 1) Prepare cooler(s) for shipment.
 - Tape drain(s) of cooler shut
 - Place mailing label with laboratory address on top of cooler(s).
- 2) Arrange sample containers in a manner to prevent potential sample container breakage.
- 3) Confirm the bottle labels are completed correctly. Place clear tape over bottle labels to prevent moisture accumulation from causing the label to peel off.
- 4) Seal sample containers within plastic zip-lock bags to prevent packing material from contacting samples.
- 5) Place packing material at the bottom of the cooler to act as a cushion for the sample containers.
- 6) Fill remaining spaces with packing material.
- 7) Confirm containers are firmly packed in cooler.



- 8) If ice is required to preserve the samples, cubes should be repackaged in double zip-lock bags, and placed on top of the packing material.
- 9) Sign COC form (or obtain signature) and indicate the time and date it was relinquished to Federal Express or other carrier, as appropriate.
- 10) Separate copies of COC forms. Seal proper copies within a large zip-lock bag and tape to inside lid of cooler. Retain copies of forms in-house.
- 11) Close lid and latch.
- 12) Tape cooler shut on both ends, making several complete revolutions with strapping tape.
- 13) Relinquish to Federal Express or other courier service. Retain airbill receipt for project records (Note: Samples will be shipped for "NEXT DAY" delivery).

If samples are delivered directly to the laboratory, or the laboratories in-house courier, by the sampling team, the packaging/shipping requirements may be omitted. COC procedures; however, must be strictly maintained.

2.4 SAMPLE MANAGEMENT AND CHAIN-OF-CUSTODY

COC procedures document the history of sample containers and samples from the time of preparation of sample containers through sample collection, shipment, and analysis. A sample is considered in custody if:

- The sample is in the sampler's physical possession
- The sample is secured by the sampler to prevent tampering
- The sample is secured by the sampler employee in an area that is restricted to authorized personnel.

To maintain a record of sample collection, transfer between personnel, shipment, and receipt by the laboratory, a COC record will be completed for each sample at each sampling location. Each time the samples are transferred, signatures of the person relinquishing and receiving the samples, as well as the date and time, will be documented.

Parallel field notebook/Groundwater Sampling Log and COC records will be maintained. Recorded information will include:

- Sampling Location
- Time and Date
- Sampling Method
- Method of Preservation.

Additionally, the field notebook will also include information on weather conditions, depth to water, total depth of the well, field parameter and instrument calibration records and other useful or pertinent information. The notebook will be kept at the facility or with their designated contractor.

2.5 QUALITY ASSURANCE/QUALITY CONTROL (QA/QC) MEASURES

Field QA/QC procedures will consist of collecting one equipment blank (if reusable equipment is used) and one duplicate sample (one additional sample from one of the wells) for each sampling event. The duplicate sample will be assigned a separate sample identification and submitted to the laboratory "blind".

The procedure for collecting an equipment blank will be to pass distilled water through the decontaminated sampling device into a laboratory-supplied sample bottles. An equipment blank sample will not be required if disposable sampling equipment is used.



3 REFERENCES

USEPA Low-Flow (Minimal Drawdown) Groundwater Sampling Procedures (EPA/540/S -95/504).

USEPA (Region 1) Low Stress (low flow) Purging and Sampling Procedure for the Collection of Groundwater Samples from Monitoring Wells (EQASOP-GW 001), January 19, 2010.

USEPA RCRA Groundwater Monitoring: Draft Technical Guidance (EPA/530-R-93-001).

MDEQ RRD Operational Memorandum No. 2: Sampling and Analysis.



Attachment C

GHD Groundwater Sampling Procedure



GHD Field Training Manual

Section 7.0

Water Sampling Standard Operating Procedures

- A. Groundwater
- B. Residential
- C. Surface Water

(T104)

200010 | Report No 2 | Revision 0 | July 1 2015



Please Adhere to the Following Quality System Training Requirements:

- Employees who are required to conduct a specific field activity must be properly certified to do the work.
- This involves reviewing the SOP and completing the online training course and exam.
- Employees must also conduct this field work under supervised conditions on at least three occasions, and must be certified by a qualified mentor. Only then can an employee conduct a specific field activity on their own. This is documented on a Field Method Training Record (QSF-021).
- Complete the QSF-021 and forward it to trainingrecords-northamerica@ghd.com.
- Please note that three topics are discussed in this SOP. A separate QSF-021 is required for each topic:
 - Groundwater Sampling
 - Residential Water Sampling
 - Surface Water Sampling



Table of Contents

7.	Water Sampling (Groundwater, Residential, and Surface Water)	
	Standard Operating Procedures	1
7.1	Introduction	1
7.2	Background	2
7.3	Planning and Preparation	3
7.4	Safety and Health	4
7.5	Quality Assurance/Quality Control	5
7.6	Equipment Decontamination	6
7.6.1	Purge Water and Decontamination Fluid Disposal	6
7.7	Field Procedures for Groundwater Sampling	7
7.7.1	Well Identification and Inspection	7
7.7.2	Air Monitoring	8
7.7.3	Water Level Monitoring/Well Depth Sounding	8
7.7.4	Well Volume Calculation	9
7.7.5	Well Purging and Stabilization Monitoring	10
7.7.5.1	Typical Method	10
7.7.5.2	Purging Entire Water Column	11
7.7.5.3	Low-Flow Purging (LFP) Technique	12
7.7.5.4	Sampling Techniques	14
7.7.5.5	Order of Sample Collection	14
7.7.6	Sample Acquisition and Transfer	15
7.7.6.1	Sample Labels/Sample Identification	16
7.7.7	Purging/Sampling Equipment	16
7.7.7.1	Peristaltic Pumps	16
7.7.7.2	Suction Pumps	17
7.7.7.3	Submersible Pumps	18
7.7.7.4	Air Lift Pumps	19
7.7.7.5	Bladder Pumps	19
7.7.7.6	Inertia Pumps	20
7.7.7.7	Bailers	20
7.7.7.8	Passive Diffusion Bags	21
7.7.8	Filtering of Groundwater Samples	22
7.8	Field Procedures for Residential Sampling	22
7.8.1	General	22
7.8.2	Field Procedures	22
7.8.3	Field Notes for Residential Sampling	23
7.9	Field Procedures for Surface Water Sampling	24
7.9.1	General	24
7.9.2	Surface Water Sample Location Selection	24
7.9.2.1	Rivers, Streams, and Creeks	25
7.9.2.2	Lakes, Ponds, and Impoundments	25
7.9.3	Sampling Equipment and Techniques	26
7.9.4	Field Notes for Surface Water Sampling	27



Table of Contents

7.10 Follow-Up Activities.....	28
7.11 References.....	29

Figure Index

Figure 3.8 Typical Groundwater/Residential Water Sample Log Entry

Forms Index

SP-02	Project Planning, Completion and Follow-Up Checklist
SP-05	Groundwater Sampling Equipment and Supply Checklist
SP-06	Well Development, Purging, and Sampling Form
SP-08	Sample Collection Data Sheet - Groundwater Sampling Program
SP-09	Monitoring Well Record for Low-Flow Purging
SP-17	Equipment and Supply Checklist - Surface Water Sampling, Sediment Sampling, and Flow Measurement

Quality System Forms Index

QSF-012	Vendor Evaluation Form
QSF-014	Field Equipment Requisition Form
QSF-019	Property Access/Utility Clearance Data Sheet
QSF-021	Field Method Training Record
QSF-030	Safety and Health Schedule (Canada)
QSF-031	Safety and Health Schedule (U.S.)



7. Water Sampling (Groundwater, Residential, and Surface Water) Standard Operating Procedures

7.1 Introduction

Groundwater, residential, and surface water sampling are conducted in order to characterize the groundwater and surface water quality at a site. Standard Operating Procedures (SOPs) are presented herein for the collection of groundwater and surface water samples from:

- Monitoring wells
- Residential wells
- Surface water bodies

This guideline is not intended to provide the basis for designing a groundwater or surface water monitoring program, but instead assumes that a groundwater and/or surface water monitoring program has already been designed. It is also assumed that a site-specific Work Plan has been established and that a GHD representative is preparing to mobilize to the site.

Groundwater and surface water sampling procedures vary from project to project due to:

- Different chemicals of concern.
- Different guidance provided by local, provincial/state, and/or federal regulatory agencies with jurisdiction at the site.
- The specific objectives of the project.

It is essential that all groundwater, residential, and surface water sampling activities conform to local, state/provincial, and federal regulations. Therefore, it is essential that the GHD representative carefully reviews the Work Plan requirements. The primary goal of groundwater, residential, and surface water sampling is the collection of samples representative of the hydrostratigraphic unit and/or surface water body. It is necessary to use appropriate sampling techniques to collect representative samples that provide reliable and reproducible results in accordance with the Work Plan and all relevant regulations.

The remainder of this section is organized as follows:

- Section 7.2 Background
- Section 7.3 Planning and Preparation
- Section 7.4 Safety and Health
- Section 7.5 Quality Assurance/Quality Control
- Section 7.6 Equipment Decontamination
- Section 7.7 Field Procedures for Groundwater Sampling



- Section 7.8 Field Procedures for Residential Sampling
- Section 7.9 Field Procedures for Surface Water Sampling
- Section 7.10 Follow-Up Activities
- Section 7.11 References

7.2 Background

The objective of a groundwater and residential monitoring program is to obtain samples that are representative of existing groundwater conditions, or samples that retain the physical and chemical properties of groundwater in the hydrostratigraphic unit. Surface water sampling is performed to collect samples that are representative of physical and chemical properties of surface water bodies. Improper sampling and transport practices will cause compounds of interest to be removed or added to a sample prior to analysis. The importance of proper and consistent field sampling methods cannot be over emphasized. It is equally important that proper documentation occurs throughout the sampling program.

The most important aspect of groundwater sampling is the collection of groundwater samples that are free of suspended silt, sediment, or other fine-grained material. Fine-grained material has a variety of chemical compounds sorbed to the particles or has the ability to sorb chemicals from the aqueous phase. This causes a bias in the subsequent analytical results. Reproducible and reliable analytical data are invaluable to a groundwater monitoring program. GHD frequently criticizes the sampling activities completed by others due to the collection and analyses of turbid samples. This SOP discusses sampling protocols that typically achieve sediment-free samples.

When sampling for monitored natural attenuation (MNA) parameters, more stringent protocols are followed to ensure sediment-free samples that are representative of the total mobile load (i.e., dissolved and naturally suspended particles). Low-flow purging (LFP) techniques are strongly recommended, if not mandated, when collecting groundwater samples for MNA parameters. The LFP techniques detailed in Section 7.7.5.3 are in accordance with United States Environmental Protection Agency (USEPA) LFP procedures (Puls and Barcelona, 1996).

Groundwater sampling is required for various reasons, including:

- Investigating potable or industrial water supplies
- Tracking contaminant plumes
- Investigating a site with suspected groundwater contamination

Groundwater is usually sampled from in-place wells, installed either temporarily or permanently. Municipal, industrial, or residential wells may also be sampled during an investigation. When completing residential well sampling it is important that representative samples are collected. Poor or incorrect sampling techniques will result in erroneous results. Incorrect results disclosed to the public will create a false impression, making it difficult to change the perception when correct results are reported.



Groundwater and residential sample collection are performed from non-impacted to most impacted locations. This eliminates the potential for cross-contamination. A review of all historical analytical data is performed to ensure the exact sampling sequence.

Surface water sampling locations are selected based on many factors including:

- The study objectives
- The location of point source discharges
- The location of no-point source discharges and tributaries
- The presence of structures (e.g., bridges, dams)
- Accessibility

Surface water sampling should be performed from downstream to upstream locations. This ensures that surface water sampling activities do not cause suspended sediments to bias samples collected downstream.

7.3 Planning and Preparation

Prior to groundwater, residential, and surface water sampling:

1. Review the Work Plan, project documents, and Site-Specific Health and Safety Plan (HASP) with the Project Manager/Coordinator.
2. Review the Quality Assurance Project Plan (QAPP) with the Project Coordinator and Project Chemist to determine Quality Assurance/Quality Control (QA/QC) and decontamination requirements.
3. Complete a Field Equipment Requisition Form (QSF-014). Assemble all sampling equipment and supplies required per the Groundwater Sampling Equipment and Supply Checklist (Form SP-05). The Project Planning, Completion, and Follow-Up Checklist (Form SP-02) should be used for guidance throughout the project.
4. Assemble the site plan, well logs, and previous sampling/purging data required for the sampling event. Determine the exact number and locations of wells to be sampled.
5. Obtain all forms to record purging and sampling activities (Forms SP-06, SP-08, and SP-09).
6. Confirm with the Project Manager/Coordinator that a Property Access/Utility Clearance Data Sheet (QSF-019) has been completed. For residential sampling, ensure that homeowners have been notified of the intended sampling event. Confirm the presence of any dogs on site, modify the site-specific Job Safety Analysis, if there is a dog.
7. Arrange access to the site. Obtain all well and site keys. Consider site access conditions (e.g., snow).
8. For surface water sampling consider if hazards exist due to deep/fast moving water, difficult access, and if additional GHD personnel are required for safety and health reasons.



9. For residential sampling contact homeowners to make arrangements for a site visit, arrange for site dog to be removed from all areas where a GHD employee will be working. The client of another party may be responsible for making arrangements.
10. Complete a Vendor Evaluation Form (QSF-012) and file in the Project file for any Vendors that do not have full approval status or are not listed on the Approved Vendor List (QSL-004). Completion of a Safety and Health Schedule (QSF-030 for Canadian work; QSF-031 for U.S. work) is necessary for all Vendors who complete field services. Prior to mobilization on site, the Vendor must submit the form to the Regional Safety and Health Manager for review and approval (if not already posted on QSL-004).
11. Contact the GHD Chemistry group to arrange:
 - SSOW (Simplified Scope of Work)
 - Laboratory
 - Sample containers delivery
 - Preservatives if required
 - Filtration information if required
 - Coolers
 - Shipping details
 - Sample starting date
 - Expected duration of sampling program
12. If several sampling events are planned, evaluate with the client the benefit of purchasing and installing dedicated sampling equipment. Dedicated purging and sampling equipment reduces potential cross-contamination and reduces decontamination requirements. At a minimum, sample tubing is dedicated to each well and is left secured in the well for future use. For LFP it is recommended that each well is dedicated with a bladder pump and tubing to eliminate well disturbance.
13. Evaluate sample notification needs with the Project Coordinator. Have the regulatory groups, client, landowner, GHD personnel, and laboratory been notified of the sampling activities?
14. Evaluate containment and disposal requirements for purge waters.
15. Plan sampling activities to ensure that wells that historically go dry or have poor recharge fit into the sampling program. This will reduce the time required for sample collection.
16. Plan the sequence of sampling activities to reduce the potential for cross-contamination. For groundwater sampling, start with clean wells and progress to impacted wells. For surface water sampling, start downstream and progress upstream.

7.4 Safety and Health

GHD is committed to conducting field activities in accordance with sound safety and health practices. GHD adheres to high safety standards to protect the safety and health of all employees,



subcontractors, customers, and communities in which they work. The safety and health of our employees takes precedence over cost and schedule implications.

Field personnel are required to implement the Safety Means Responsibility Awareness Teamwork (SMART) program as follows:

- Assure the HASP is specific to the job and approved by a Regional Safety & Health Manager.
- Confirm that all HASP elements have been implemented for the job.
- A Job Safety Analysis (JSA) for each task has been reviewed, modified for the specific site conditions, and communicated to all appropriate site personnel. The JSAs are a component of the HASP.
- Incorporate Stop Work Authority; Stop, Think, Act, Review (STAR) process; Safe Task Evaluation Process (STEP); Observations process; Near Loss and Incident Management process in the day-to-day operations of the job.
- Review and implement applicable sections of the GHD Safety & Health Policy Manual.
- Confirm that all site personnel have the required training and medical surveillance as defined in the HASP.
- Be prepared for emergency situations, locating safety showers, fire protection equipment, evacuation route, rally point, and first aid equipment before you begin working, and make sure that the equipment is in good working order.
- Maintain all required Personal Protective Equipment (PPE), safety equipment, and instrumentation necessary to perform the work effectively, efficiently, and safely.
- Be prepared to call the GHD Incident Hotline at 1-866-529-4886 for all involving injury/illness, property damage, vehicle incident, and/or significant Near Loss.

It is the responsibility of the Project Manager to:

- Ensure that all GHD field personnel have received the appropriate health and safety and field training and are qualified to complete the work.
- Provide subcontractors with a Job Hazard Analysis to enable them to develop their own HASP.
- Ensure that all subcontractors meet GHD's (and the Client's) safety requirements.

7.5 Quality Assurance/Quality Control

A well-designed QA/QC program will:

- Ensure that data of sufficient quality are obtained, for proper site management decisions or remediation design.
- Allow for monitoring of staff and contractor performance.
- Verify the quality of the data for the regulatory agency.

It is important to note that a QA/QC program should be developed on a site-specific basis. QA/QC requirements are discussed in Section 3.9.



7.6 Equipment Decontamination

Equipment decontamination procedures for a groundwater, residential, or surface water monitoring program will be described in detail in the site-specific Work Plan or in the QAPP.

Equipment is decontaminated between sampling locations and prior to leaving the site. Upon completion of the sampling program, all equipment is decontaminated at the site and then returned clean to the appropriate field equipment manager.

For most groundwater, residential, and surface water sampling programs, sampling equipment (e.g., pumps, bailers, water level indicators) is typically cleaned as follows:

1. Wash with clean potable water and laboratory detergent, using a brush as necessary to remove particulates.
2. Rinse with tap water.
3. Rinse with deionized water.
4. Air dry for as long as possible.

If required, the following steps may be added when sampling for Volatile Organic Compounds (VOCs) and metals:

1. Rinse with 10 percent nitric acid (only if samples are to be analyzed for metals).
2. Rinse with deionized water.
3. Rinse with appropriate solvent (pesticide grade isopropanol, methanol, acetone, hexane, if required).
4. Rinse again with deionized water.
5. Air dry for as long as possible.
6. Wrap samplers in aluminum foil to prevent contamination.

Caution: Check the QAPP to confirm the cleaning protocol. Use of incorrect cleaning protocol could invalidate chemical data.

7.6.1 Purge Water and Decontamination Fluid Disposal

Project-specific disposal methods for purged groundwater and decontamination fluids are determined by the Project Manager during the sampling program's planning and preparation stage (see Section 7.3), but may include:

1. Off-site treatment at private treatment/disposal facility or publicly owned treatment facilities (sanitary sewer).
2. On-site treatment at a client-operated facility.
3. Direct discharge to the surrounding ground surface, allowing infiltration to the underlying subsurface.
4. Direct discharge to an impervious pavement surface allowing for evaporation.



Options 3 and 4 are permitted only after careful review of these practices and the anticipated site conditions. Under no circumstances shall GHD personnel aggravate an existing condition or spread contamination into clean areas.

Decontamination fluids (specifically cleaning solvents/acids) are segregated and collected separately from wash water and purge water. Often small volumes of solvents used during the course of a groundwater, residential, or surface water sampling program will evaporate if left in an open pail. If evaporation is not possible, off-site disposal need to be arranged.

7.7 Field Procedures for Groundwater Sampling

The typical series of events that takes place for a groundwater sampling program is:

1. Well identification and inspection
2. Air monitoring
3. Water level monitoring
4. Well depth sounding
5. Well volume calculation
6. Purging and sampling equipment installation
7. Well purging and stabilization monitoring
8. Sample collection, sample preparation, completion of chain-of-custody, (COC) sample packaging
9. Final water level monitoring (if required), purging, sampling equipment removal, secure the well
10. Equipment decontamination
11. Field note completion and review
12. Sample shipment and COC distribution
13. Purged groundwater and decontamination fluid disposal
14. Sample record documentation, equipment return
15. Completion and distribution of appropriate forms

It is recommended that new plastic sheeting be placed on the ground around the well to prevent contamination of purging and sampling equipment and accessories (e.g., pumps, hoses, rope.).

7.7.1 Well Identification and Inspection

At sites with numerous wells or wells nests, misidentification of wells has occurred. The GHD representative must be alert to the possibility of potential cap switching, mislabeled wells, or unlabeled well locations.



Determine proper well location and identification by comparing the well log details to the measured well depths (i.e., total well depth, casing diameter, casing stick-up, or stick-down distances), field tie-ins, and site plan.

Once well identification has been established, complete a thorough well inspection:

1. Determine if the well cap and lock are secure, and check for vandalism.
2. If no lock is present, dedicate a new lock to the well location.
3. Examine the integrity of the surface seal.
4. Check for cracks, evidence of frost heave, or subsidence in the vicinity of the well.
5. Examine the integrity of the protective casing. Ensure that the casing can be closed and locked.
6. If required, re-label the well to assist in future identification.
7. If the well is installed with dedicated sampling equipment, check for cracks or leaks in tubing, and worn or frayed rope.
8. Record all the well inspection details in the field book to document well conditions and suitability for groundwater sampling activities.
9. Forward the well inspection results to the Project Coordinator, especially if repairs are required.

7.7.2 Air Monitoring

Prior to removing a well cap, measure the breathing space above the well with a photoionization detector (PID) to establish background of undifferentiated organic vapor levels. Repeat this process once the well cap has been removed. If either of the PID levels exceed the air quality criteria established in the HASP, air-purifying respiratory (APR) protection or a supplied air system is required. Also take a PID reading inside the riser pipe. This PID reading is a good indication of elevated chemical or non-aqueous phase liquids (NAPL) presence. Report all elevated PID levels to the Project Coordinator immediately to determine if additional health and safety and personnel protective equipment is required. The HASP will provide the required action levels and PPE.

7.7.3 Water Level Monitoring/Well Depth Sounding

Prior to commencing well purging and groundwater sampling, the water level is measured for hydraulic monitoring and to determine the well volume. Typically, a complete round of water level measurements is taken at a site to establish groundwater conditions prior to initiating well purging or groundwater sampling activities.

A watertight cap provides an airtight seal on the casing and the water level positioned in the casing area. The cap creates a vacuum or pressurized condition in the casing section which can support or depress the water column in the well casing. This can produce an artificially high or low water level in the well casing. This effect can cause a few inches or feet of error in the static water level. Once the cap is removed, allow the pressure to stabilize for about a half hour. Measure the water level



frequently to ensure that stabilization of the water level has occurred. Once the water level has stabilized (i.e., is static) the correct water level may be measured.

A number of instruments are available to measure groundwater levels. GHD typically uses:

- Battery-operated water level indicators (i.e., audible and/or visual identification of water level)
- Battery-operated oil/water interface probes (i.e., audible and/or visual identification of water levels and presence of NAPL)
- Electronic transducers (numerous manufacturers) and recording devices for long-term hydraulic monitoring
- Stevens™ recorders (both float and electronic instrumentation) for long-term hydraulic monitoring

Section 8.0 describes in detail the equipment and monitoring techniques for water level measurements.

Well depth sounding is often required to confirm well identification, evaluate the accumulation of sediment in the well bottom, or assist in determining the standing well volume. Sounding is performed using a water level indicator or a measuring tape with a weighted end. The water level indicator or weighted tape is lowered to the bottom of the well and a comparison is made of the installed well depth versus the measured well depth. The presence of excessive sediment or drill cuttings may warrant redevelopment of the well prior to well purging and groundwater sampling activities.

The total well depth is compared to the original installed total well depth. If the well screen is more than 50 percent blocked by accumulated sediment, the well is redeveloped prior to the next groundwater sampling event. Report all wells requiring redevelopment to the Project Coordinator. Well depth sounding is performed on an annual or biannual basis if the well is equipped with a dedicated pump.

For LFP, well depth measurement is performed to ensure proper pump intake placement. The use of a wide-based probe, such as a weighted tape, is necessary to minimize penetration and disturbance of accumulated sediment. The measuring device is lowered slowly through the water column to the well bottom to minimize mixing of the stagnant well casing water and disturbance of sediment.

Note: Don't forget that decontamination procedures apply to the water level monitoring equipment as well as the groundwater sampling equipment. If well sounding is performed, the entire measuring device must be thoroughly decontaminated prior to re-use. Measuring the well depth with certain water level indicators may damage the probe seal. Therefore, a tape with a weighted end should be used to measure well depth.

7.7.4 Well Volume Calculation

Prior to commencing well purging, the volume of water in the well must be known to determine the volume of groundwater to be removed. A well volume is defined as the volume of water contained in



the well screen and casing (and in the case of an open bedrock hole, the volume of water in the open corehole and possibly in the well casing). To determine the standing water volume in a well:

1. Calculate the distance from the bottom of the well to the static water level.
2. Measure the inside diameter of the well or casing. Obtain the volume of standing water in the well using the following formula:

$$V = \pi r^2 h \text{ (7.48 U.S. gallons/cubic feet) (1 liter/1,000 cubic centimeters)}$$

Where:

V = volume of water in gallons or liters

π = 3.142

r = radius of well casing (feet or meters)

h = depth of water column in the well (feet or meters)

Typical 1 - Foot Casing Volumes	
Diameter (inches)	Gallons (U.S.) of Water Per Foot of Casing
1.5	0.09
2	0.16
3	0.37
4	0.65
6	1.47

Typical 1 Meter Casing Volumes		
Diameter		Litres per Meter of Casing
(inches)	6 (cm)	
1.5	3	1.14
2	5	2.02
3	8	4.56
4	10	8.11
6	15	18.24

7.7.5 Well Purging and Stabilization Monitoring

7.7.5.1 Typical Method

Prior to initiating groundwater sample collection, the wells is purged of the standing stagnant groundwater volume. This volume is not representative of the groundwater in the hydrostratigraphic unit. Purging is performed until the water in the well is representative of the actual conditions in the hydrostratigraphic unit. Stabilization is usually achieved by the removal of three to five times the volume of standing water in the well (USEPA convention). Purging is considered complete once purged groundwater is free of sediment and field parameters including specific conductance, temperature, and turbidity are stable. Stabilization is achieved when field measurements for specific conductance and temperature are within a range of plus or minus 10 percent of the average for the



last three readings. Field measurement for pH should be within a range of plus or minus 0.1 pH unit of the average for the last three readings, and groundwater turbidity values should be less than 5 nephelometric turbidity units (NTU) (guidance value only). Once the number of well volumes required to achieve stabilization is established, the volume required to reach stabilization for future sampling events is reduced or eliminated. Extended purging of a well will generally result in achieving sediment-free groundwater conditions.

During purging, if stabilization has not occurred after removal of five well volumes, purging is continued until ten well volumes have been removed. If stabilization still has not been achieved, stabilization may be dropped as a pre-condition to groundwater sampling. The Project Coordinator should be notified that stabilization has not occurred after the removal of ten well volumes.

At high yielding wells, removing three to five well volumes is usually sufficient prior to initiating groundwater sampling. For low yield wells (i.e., wells that pump dry after one well volume) it is necessary to purge the well dry on three successive days, unless the well recovers to full static conditions in a shorter time. If the recharge is relatively high, groundwater sampling will be initiated once the well has fully recovered to static groundwater conditions, or to a level that is sufficient to collect the necessary groundwater sample volume.

Note: Purging of dry wells should be scheduled to begin on Monday or Tuesday, to reduce weekend requirements.

Turbidity of purged groundwater is evaluated by a visual examination for sediment/silt presence or by using a nephelometer which physically measures groundwater turbidity in NTUs. Generally, a turbidity value of 50 NTU or less is acceptable, although some regulatory agencies have established lower criteria (i.e., less than 5 NTU). If 50 NTU is not achieved, filtration of samples may be required. LFP can generally result in turbidity values less than 5 NTU.

Note: Agitation of the water column within the well will increase turbidity. Therefore, bailers and inertia pumps (Waterra™) are of limited use for collecting sediment-free samples. The tubing of peristaltic pumps must be secured to prevent movement of the tubing within the water column which would disturb sediment. The best method to reduce sediment disturbance is low-volume non-agitation pumping (i.e., bladder pump).

Well purging is accomplished using dedicated equipment or by using either peristaltic, bladder, or other approved purging methods. Purging and sampling equipment are dependent on the total well depth. Bailing can be used for well purging but this method stirs up sediment and increases the purging effort required before stabilization is achieved. Equipment available for well purging is discussed in Section 7.7.7. Monitoring equipment used during well purging includes a water level indicator, pH meter, thermometer, conductivity meter, and turbidity meter.

7.7.5.2 Purging Entire Water Column

The purging equipment is lowered into the top of the standing water column. Well purging is completed from as close to the top of the water column as possible, not from the well bottom, unless poor well recovery occurs. Purging from the top of the water column moves water from the formation through the well screen of the well and into the well casing. This allows for the entire



static volume to be removed. Purging at depth in the water column does not remove water above the pump intake and results in the collection of unrepresentative samples.

If required, the pump intake can be adjusted. If the recovery rate is greater than the pumping rate, the pump should remain suspended until the required purged volume has been removed. If the recovery rate is less than the pumping rate, the pump should be lowered to ensure the removal of the required well volume.

7.7.5.3 Low-Flow Purging (LFP) Technique

LFP purging results in minimal drawdown during well purging, so less purging is required before formation water is removed. The volume required for purging using LFP is significantly reduced. LFP results in less agitation and mobilization of sediments compared to traditional sampling techniques.

A pre-cleaned stainless steel bladder pump equipped with a Teflon™ bladder is strongly recommended for LFP. The discharge line should be polyethylene or Teflon™ lined tubing with an inside diameter of 1/4 or 3/8 inch (6 or 10 mm). Check the Work Plan or QAPP to ascertain the proper bladder and discharge tubing. Smaller discharge tubing ensures that the tubing remains filled with water and reduces air bubbles at low purging rates. The airline to the pump is generally 1/4-inch (6 mm) inside diameter polyethylene tubing. The pump is secured to nylon rope and positioned in the well so that the pump intake is set at the mid-point of the well screen, or a minimum of 2 feet (0.6 m) above the bottom of the well or accumulated sediment level. It is important that the rope, airline, and discharge tubing are measured prior to installation in the well. The bladder pump and tubing are lowered very slowly through the water column to minimize mixing of the stagnant well casing water and to minimize the agitation of sediment into suspension, which would increase the purging time. It is recommended, and in some instances regulated, that pump installation occurs at least 24 hours prior to initiating LFP. It is recommended that a bladder pump be dedicated to the well for regular monitoring events.

During LFP, the pumping rate should be between 100 and 500 milliliters per minute (mL/min). It is recommended that initial pumping be conducted at a lower rate to limit drawdown in the well. During purging, groundwater levels are measured to maintain a maximum 0.4 foot (0.1 m) of drawdown. The pumping rate can be gradually increased during LFP. Pumping rate increases will be dependent on the drawdown and the stabilization of field parameters discussed below. Pumping rate adjustments should occur in the first 15 minutes of purging. After this time the pumping rate should remain constant and flow rate adjustments should be avoided. During purging, the pumping rate and groundwater level should be measured at least every 10 minutes. It is recommended that water level measurements occur at 5-minute intervals.

During LFP, stabilization of the purged groundwater is required to ensure the collection of representative groundwater samples from the formation and not from the stagnant water in the well casing. Field parameters including pH, temperature, specific conductance, oxidation-reduction potential (ORP), dissolved oxygen (DO), and turbidity should be monitored during LFP. The measurement of these field parameters is used to evaluate if stabilization of the purged groundwater has occurred prior to the collection of groundwater samples. The field measurements should be measured and recorded at 5-minute intervals. Groundwater stabilization is considered



achieved when three consecutive readings for each of the field parameters, taken at 5-minute intervals, are within the following limits:

pH	±0.1 pH units of the average value of the three readings
Temperature	±3 percent of the average value of the three readings
Conductivity	±0.005 milliSiemen per centimeter (mS/cm) of the average value of the three readings for conductivity <1 mS/cm and ±0.01 mS/cm of the average value of the three readings for conductivity >1 mS/cm
ORP	±10 millivolts (mV) of the average value of the three readings
DO	±10 percent of the average value of the three readings
Turbidity	±10 percent of the average value of the three readings, or a final value of less than 5 NTU

During LFP, field parameters are measured using a flow-through cell apparatus. At the start of LFP the purge water is visually inspected for clarity prior to connecting to the flow-through cell. If the purge water is turbid, LFP continues until the purge water is visually less turbid prior to connecting to the flow-through cell. Field parameters may be obtained using individual meters or a multiple meter unit; however, the use of a flow-through cell is highly recommended. All meters must be calibrated daily in accordance with the manufacturer's and GHD's calibration instructions, and a calibration record maintained in a standard GHD field book.

During LFP the meter readings are monitored for evidence of meter malfunction. The following are common indicators of meter malfunctions:

- DO above solubility (e.g., oxygen solubility is approximately 11 milligrams per liter (mg/L) at 10°C) may indicate a DO meter malfunction.
- Negative ORP and DO less than 1 to 2 mg/L may indicate either an ORP or a DO meter malfunction (i.e., should have positive ORP and DO less than 1 to 2 mg/L under oxidizing conditions).
- Positive ORP and DO less than 1 mg/L may indicate either an ORP or a DO meter malfunction (i.e., should have a negative ORP and DO less than 1 mg/L under reducing conditions).

Meter calibration fluids should be available for meter recalibration in the field. Spare meters should also be available for meter replacement if necessary.

Note: DO levels exceeding the solubility of oxygen in water are erroneous and are indicative of meter malfunction or poor sampling techniques causing turbulence and aeration. DO concentrations cannot exceed:

9 mg/L at 20°C 10 mg/L at 15°C 11 mg/L at 10°C 14 mg/L at 1°C

Stabilization will be considered complete when the field parameters have stabilized as indicated in the above table. Purging will continue if stabilization does not occur, until a maximum of 20 screen volumes has been removed. LFP causes groundwater to be drawn from a significant distance above or below the pump intake. Therefore, the screen volume is based on a 5-foot (1.5 m) screen length. After the removal of 20 screen volumes, purging will continue if the purged water remains



visually turbid and appears to be clearing. Also purging will continue if the field parameters vary only slightly outside of the stabilization criteria and appear to be approaching stabilization.

If the recharge to the well is insufficient to conduct LFP, the well should be pumped dry and allowed to recharge sufficiently for the collection of the groundwater sample volume. Wells purged dry are required to meet the stabilization criteria detailed above.

7.7.5.4 Sampling Techniques

Upon completion of purging, with groundwater stabilization and clarity meeting the applicable protocol described above, groundwater sample collection can proceed. Generally the field parameters of pH, temperature, and specific conductance are monitored first, then any other required field measurements.

Samples are collected directly from the purging pump, when possible, or an alternate device (i.e., pump or bailer) may be installed or used. If new sampling equipment is installed, the first few bails or discharge volumes should be discarded to allow acclimation of the sampling equipment with the groundwater.

Samples are typically collected from the pump or bailer with the discharged groundwater collected directly in the appropriate sample containers. The interior of the bottle or cap must not be touched or handled in anyway. New gloves (i.e., disposable nitrile gloves or equivalent) should be worn for the collection of each sample. Caps from sample bottles must not be placed on the ground or in pockets to eliminate the possibility of cross-contamination.

Descriptions of the various equipment and sampling methods for the collection of groundwater samples are contained in Section 7.7.7.

The following describes the main activities involved in the collection of groundwater samples.

7.7.5.5 Order of Sample Collection

Groundwater samples are collected and containerized in the order following volatilization sensitivity:

1. VOCs
2. Semi-volatile organic compounds (SVOCs)
3. Total organic carbon
4. Total organic halides
5. Extractable organics
6. Total metals
7. Dissolved metals
8. Phenols
9. Cyanide
10. Sulfate and chloride



11. Nitrate and ammonia
12. Microbiological parameters
13. Radionuclides

QA/QC requirements for groundwater sampling are described in detail in Section 3.9.

7.7.6 Sample Acquisition and Transfer

If groundwater sample collection is performed using a pump, the flow rate must not exceed 100 mL/min during the collection of groundwater samples for VOCs. The low flow rate will reduce the possibility of degassing samples. During the collection of groundwater into the sample container or filtration device, minimize agitation and aeration of the sample. Groundwater samples are transferred directly into the sample container for submittal to the laboratory. Groundwater samples should not be collected in larger containers and subsequently transferred to smaller sample containers; however, on occasion this will be required for filtration or sample composting. During VOC sample collection, samples must not be collected, handled, or containerized near or in the vicinity of a running motor or exhaust which may contaminate the samples.

Groundwater samples for VOCs are collected in laboratory supplied 40 mL glass vials. The vials are filled to the top until a meniscus is formed, then topped with a Teflon™-lined cap. To prevent the loss of volatiles, it is important that no air bubbles or headspace are present in the sample container. Inverting and tapping the vial will check for the presence of air bubbles. If air bubbles are present, the sample should be topped off again and resealed. This process may only be performed a maximum of twice, at which time the sample must be discarded and the sample retaken. If preservatives were present in the bottle from the laboratory, a new sample vial must be used.

Note: Gas bubbles that appear in VOC containers after sample collection may be a result of degassing or reaction with preservative. If this occurs, note this occurrence on the chain-of-custody. Re-sampling is not required in most cases.

During sample collection ensure groundwater samples are preserved according to laboratory requirements. If required and supplied by the laboratory, preserve the samples in accordance with the QAPP. Some laboratories pre-preserve bottles so that once the groundwater sample is added the preservation is completed. In either case, it is advisable to check sample preservation using litmus paper. Using litmus paper ensures that groundwater sample preservation has been completed to the proper pH as required by the QAPP. If preservation of a sample does not meet the requirements of the QAPP, it may be necessary to add additional preservative, or note on the chain-of-custody that incomplete sample preservation has occurred.

Once sample collection is complete, samples are placed in a cooler on ice to maintain a sample temperature no more than 4°C.



7.7.6.1 Sample Labels/Sample Identification

Label all groundwater samples with the following, written in indelible ink:

1. A unique sample number (see Section 3.9 for guidance)
2. Date and time
3. Parameters to be analyzed
4. Job number
5. Sampler's initial

Secure the label to the bottle. It is recommended that bottle labels be covered with wide clear tape to protect the label during sample packing and shipment. Pack glassware in appropriate packing material to deter breakage during sample packing and shipment. Sample labels can be prepared in advance in GHD offices that have label-generating programs.

An example of a groundwater sample log entry is provided on Figure 3.8.

Section 3.9 details sample labeling requirements for environmental sampling programs. Section 3.9 also details COC requirements and sample shipment requirements.

7.7.7 Purging/Sampling Equipment

GHD maintains a wide variety of purging and sampling equipment for well purging and groundwater sample collection. The groundwater sampler should be familiar with purging and sampling equipment and understand equipment limitations and proper use. Some equipment is very useful for well purging (i.e., high flow rates) but is not permissible for LFP or for sampling sensitive parameters (e.g., VOCs cannot be collected with a submersible (turbine) or suction pump). If the groundwater sampler understands the various equipment operation and limitations, the proper selection of purging and sampling equipment is made, which will minimize the purging and sampling duration and maximize productivity.

Caution: Gas powered equipment requires special attention to ensure that staff hauling these units do not cause equipment or sample contamination. Frequent changes of disposable glove as well strict separation of sampling crew tasks (i.e., those handling pumps and hoses do not contact generator or are involved in any refueling activities) are required.

The following subsections describe the equipment available for groundwater sampling, the equipment use, approximate flow rates, and advantages and disadvantages of the equipment.

7.7.7.1 Peristaltic Pumps

A peristaltic pump is acceptable for purging wells and for most groundwater sample analytes. The groundwater sampler must ensure that a peristaltic pump is acceptable to regulatory agencies with local jurisdiction for VOC and SVOC sample collection. The QAPP will provide sampling requirements.



A peristaltic pump is capable of lifting water from a maximum depth of 25 feet (7.6 m) below ground surface or the pump, whichever is greater. A peristaltic pump is a self-priming, low volume, suction pump which consists of a rotor with ball bearing rollers. Flexible silicon tubing is inserted around or in the pump rotor and squeezed in place by the heads as they revolve in a circular pattern. The section of silicon tubing must not exceed 3 feet (0.9 m) in length. Additional rigid polyethylene or Teflon™ tubing is attached to the flexible tubing and placed in the well. Another piece of rigid tubing is attached to the discharge end of the flexible silicon tubing to facilitate sample collection. The entire length of rigid and flexible silicon tubing is dedicated to the well for future use. The tubing is typically tied and suspended in the well. The flexible or rigid tubing is not reused in other wells because cross-contamination will occur.

Note: Often a length of tubing is accidentally dropped into a well and can be difficult to retrieve. Retrieval can be accomplished by sending another piece of tubing down the well overlapping the lost section of tubing. Once in place, rotate the tubing, essentially wrapping or corkscrewing the lost tubing and new tubing together. After a number of turns are completed pull the tubing, hopefully with the lost section wound around the new piece. Repeat the procedure until successful.

Liquid is pulled into the tubing by the peristaltic pump through the creation of a vacuum as the rotor head turns. An advantage of using a peristaltic pump is that no pump parts come in direct contact with the sample. A peristaltic pump is capable of providing low flow sampling rates (i.e., typically less than 500 mL/min) with less agitation than other suction pumps. However, it is important that the tubing is secured during pumping to prevent the tubing from moving and causing agitation. A peristaltic pump also allows for regulation of the flow rate by increasing or decreasing the rotor head speed.

Peristaltic pumps are small and easily mobilized to remote sample locations. They require minimal setup, and do not require decontamination between sample locations. The disadvantages of a peristaltic pump are its limited lift and flow capabilities and the limited ability to collect VOC and SVOC samples. If VOC or SVOC sampling, check the QAPP to see if sampling with a peristaltic pump is allowed. Also check with regulatory agencies with local jurisdiction to see if the use of a peristaltic pump for collection of VOC and SVOC samples is acceptable. If using a peristaltic pump for purging, and the collection of VOCs and SVOC samples with the peristaltic pump is not acceptable, it is common to collect the initial VOC and SVOC analytes with a stainless steel bottom loading bailer. The peristaltic pump can then be used to collect the remaining sample analytes.

Peristaltic pumps are becoming more popular for LFP. However, it should be noted that a peristaltic pump may cause degassing, pH modification, and possible VOC loss.

7.7.7.2 Suction Pumps

A number of suction pumps (e.g., centrifugal) exist that can be used for purging applications only. A suction pump draws water through a suction line by creating a vacuum in the suction line or hose. Once drawn into the pump, the groundwater comes into direct contact with the pump rotor/pumping chamber area and it is therefore undesirable for groundwater sampling due to high groundwater agitation. Decontamination of suction pumps is extremely difficult. As with peristaltic pumps, most suction pumps have a limited lift capability of about 25 feet (7.6 m). Larger suction pumps, like



2-inch (5 cm) trash pumps, can achieve high flow rates under low hydraulic head. Flow rates of 15 to 20 U.S. gallons per minute (USgpm) (57 to 76 liters per minute [L/min]) can be achieved. This high flow rate minimizes purging time. New or dedicated suction line should be used at each well if a suction pump is used for purging.

Large suction pumps are also useful for well development, in conjunction with agitation and surging.

Large suction pumps are not suited for LFP due to degassing, pH modifications, VOC loss, and lack of flow adjustment.

Caution: The groundwater sampler must prevent the siphoning of purged water from a bulk container back into the well. For example, the following scenario is possible: Joe Sampler has completed purging well 'xyz' and has turned off the 2-inch trash pump. The trash pump discharge line is inserted into a wastewater tank and is submerged below the tank water level. As Joe prepares his glassware and sample pump, the wastewater tank contents are siphoned back into the well. This can result in cross contamination with water from other sites/wells which have been purged either:

- into the tank
- through the pump
- through the discharge line

All discharge lines/groundwater purge pumps must be provided with a check valve to prevent this situation.

Drilling rig pumps including Moyno, progressive cavity, bean, and mud pumps can be used for well purging and well development.

Suction pumps are a useful tool for high rate purging and well development. They require no additional equipment other than a suction line and discharge line for each well. They are mobile and easily transported around and between sites. Suction pumps are limited to use in wells with less than 25 feet (7.6 m) of lift, are difficult to decontaminate, and are unsuitable for sample collection. Large suction pumps are not suitable for LFP.

7.7.7.3 Submersible Pumps

A submersible pump generally provides high discharge rates for purging at depths beyond the capabilities of a suction pump. Based on its size, a submersible pump can pump water from substantial depths at very high pumping rates and can provide higher groundwater extraction rates than other methods. At high pumping rates, a submersible pump can cause agitation and aeration. This results in some submersible pumps not being suitable for the collection of groundwater samples for VOC and SVOC analysis.

Adjustable rate submersible pumps, constructed of stainless steel or Teflon™, are suitable and approved for LFP provided low flow rates are maintained.

The submersible pump, including the electrical cable and lowering cable, must be decontaminated between wells in accordance with the Work Plan or QAPP.



A submersible pump installed in bedrock or in a deep well should be attached to rigid piping (i.e., 3/4-inch (1.9 cm) steel) to allow for pulling or pushing of the pump. The pump may need to be pushed or pulled to the appropriate installation depth, past tight spots in the well, and when affixing the electrical cable and lowering the cable/safety line. Even when rigid piping is used, a safety line must be attached to the pump in case the piping becomes unthreaded or the pump connection is lost.

Submersible pumps can provide high flow rates that are useful for deep well or large diameter well purging activities. They tend to be labor intensive because of decontamination problems, power supply, and discharge piping size. Some submersible pumps are not suitable for some sample analytes. Small submersible pumps (i.e., 2-inch (5 cm) Grundfos™) have the proper construction and have adjustable flow rates, making them suitable for LFP.

7.7.7.4 Air Lift Pumps

An air lift pump operates using compressed air or nitrogen. The compressed air or nitrogen comes into direct contact with the groundwater and forces groundwater from the pump chamber through a series of check balls into the discharge line. An air lift pump operates on alternate pump discharge and pump recharge cycles. The pump and recharge cycles are controlled using a control box at ground surface. Air lifting is possible from deep depths with moderate to low flow rates (2 to 3 USgpm [7.6 to 11.5 L/min]) depending on the pump installation depth, static head, discharge tubing diameter, and air supply pressure.

Since the air or nitrogen comes in direct contact with the groundwater, an air lift pump should not be used for the collection of groundwater samples for VOC and SVOC analysis.

An air lift pump is a good tool for deep well purging and development. If an air lift pump is used for purging, an alternate sampling method will be required (e.g., bailers or bladder pump) for the collection of VOC and SVOC groundwater samples.

7.7.7.5 Bladder Pumps

Bladder pumps, as with air lift pumps, are driven by compressed air or nitrogen but the air or nitrogen does not come in contact with the groundwater. The contact between the air or nitrogen and the groundwater is eliminated by the presence of a Teflon™, polyethylene, or natural rubber bladder. The pump operation, as with the air lift pump, is cyclic and is controlled using a control box at ground surface. The control box controls the pump filling and discharge time. Because the air or nitrogen does not come in direct contact with the groundwater, and there is limited groundwater agitation and degassing, a bladder pump is the best sampling equipment for the collection of groundwater samples for VOC and SVOC analysis.

Bladder pump operation is very quiescent, causing little formation and well disturbance. By using a bladder pump, collecting a sediment-free groundwater sample is easily achieved. An adjustable rate bladder pump should be used for LFP. Bladder pumps generally are only able to achieve a maximum pumping rate of 1.5 USgpm (5.7 L/min). It is important to note that flow rates should be reduced in deep well applications.



Well purging and sampling can be performed using a bladder pump. Once sampling is completed, the pump should be disassembled and decontaminated in accordance with the Work Plan or QAPP prior to use in other wells. The sample tubing is generally 1/4- or 3/8-inch (6 or 10 mm) diameter polyethylene or Teflon™ lined polyethylene tubing. The air line is generally 1/4-inch (6 mm) polyethylene tubing. The sample and air line tubing are typically suspended in the well for future use (dedicated). At some sites a complete sampling system (bladder pump, discharge tubing, and air line) is dedicated to each well.

Bladder pumps provide excellent sample quality and are useful in deeper sampling applications. There are no analyte restrictions. Bladder pumps are strongly recommended for LFP applications.

Bladder pumps require additional equipment including control box, compressed air or nitrogen, and tubing. The setup of a bladder pump is quite labor intensive unless a dedicated system is in place. Decontamination of a bladder pump requires pump disassembly and re-assembly. Finally, bladder pumps are not capable of high flow rates, thus purging times tend to be increased slightly.

7.7.7.6 Inertia Pumps

An Inertia pump or Waterra™ pump is a manually operated or mechanically driven pump which uses only a foot valve on the sample/purge tubing. "Jerking" the sample/purge tubing with the attached foot valve removes groundwater from the well. The rapid lifting and lowering action of the tubing imparts an inertia to the water column within the sample/purge tubing. This causes the water column to rise to ground surface and discharge from the end of the sample/purge tubing. The foot valve holds the water column in the tubing during the lifting process and allows groundwater to enter the sample/purge tubing during the lowering, or down stroke.

GHD owns both manual and mechanical gas-powered inertia systems. Flow rates with inertia pumps are variable and are dependent on cycle speed, tubing size, foot valve size, well depth, and depth to groundwater. The inertia pump is a useful method for purging and for collection of most groundwater sample analytes. Acceptability of VOC and SVOC sampling with inertia pumps is gaining approval in selected areas. Prior to using an inertia pump as a sampling device, check the sampling requirements in the QAPP, or obtain approval from the Project Coordinator.

Inertia pumps are useful for the extraction of dense non-aqueous phase liquids (DNAPL). The only equipment that is exposed to the gross contamination is the foot valve and a small section of the sample/purge tubing. On most projects, the foot valve and sample/purge tubing are dedicated to the well.

Inertia pumps tend to cause extensive disturbance to the water column. The vigorous lifting and lowering of the inertia pump tends to make it difficult to collect sediment-free groundwater samples. Therefore, inertia pumps are not suitable for LFP.

7.7.7.7 Bailers

A bailer is a manual sampling device consisting generally of a hollow tube (e.g., Teflon™, PVC, or stainless steel) with a lower check ball that permits water entry and prevents water loss. The bailer is lowered slowly into the well. This allows water to enter the bailer through the bottom, and the weight of the water inside the bailer closes the check ball when the bailer is retrieved from the well.



A rope or cable is affixed to the bailer to allow the lowering and retrieval of the bailer from the well. Bailing tends to be disruptive to the water column and formation. Obtaining sediment-free groundwater samples using a bailer tends to be difficult, if not impossible. VOCs and SVOCs, as well as other analytes can be collected using a bailer, but it is important that these analytes be as sediment-free as possible. The compatibility of the bailer material and groundwater analytes should be reviewed and approved prior to using a bailer for the collection of groundwater samples. Generally, Teflon™ bailers are acceptable for the collection of most analytes.

Power winches with overhead tripods are available to assist in purging and sampling deep or large volume wells.

Flow rates attained using a bailer is a function of the bailer size and retrieval frequency. Retrieval frequency is dependent on well depth, water depth, and well recharge rate. Bailing is not practical for deep wells or for the removal of large well volumes.

A bailer is a useful tool for well development as the surging action from the bailer insertion and removal from the well promotes sediment suspension and subsequent removal. However, obtaining completely sediment-free samples, or samples below 50 NTU, is difficult if not impossible using a bailer.

A bailer provides representative samples once the well has been adequately developed and purged. A bailer is not suitable for LFP. Rope used for bailing must be kept off the ground and free of other contaminating material that could be introduced to the well. Rope can either be dedicated to the well for future use or discarded.

7.7.7.8 Passive Diffusion Bags

When sampling with diffusion bags the well must be fully developed using an alternate method.

A diffusion bag is a polyethylene bag that contains deionized water. The bag is attached to an appropriate length of rope or cable in order to be submerged to the appropriate depth (indicated in the Work Plan, QAPP, or as instructed by the Project Coordinator). Cable or rope used to suspend diffusion bags can be dedicated to the well for future use or discarded.

Once submerged to the appropriate depth, the diffusion bag is left in the well for an extended period of time, usually 14 days, to allow the bag to equilibrate with the water in the well. The use of diffusion bags eliminates well purging prior to sampling. Placement of multiple diffusion bags in a well allows for vertical groundwater profiling.

Diffusion bags are a low cost method for the collection of groundwater samples. Advantages include:

- No purge water to dispose of.
- No equipment decontamination between wells.
- Simple logistics and operation.
- Reduction in personnel and exposure times.
- Samples collected are representative of formation water adjacent to well.



- Allow for vertical profiling of water column.
- Appropriate for long-term monitoring programs.

The disadvantage of diffusion bags is the length of equilibrium time, generally 14 days. Currently, there are membranes available for diffusion bags suitable for the collection of groundwater samples for select SVOC, and metals analyses. However, there are no membranes currently available for polychlorinated biphenyls (PCBs).

Note: Handle diffusion bags only when wearing clean nitrile or surgical gloves.

7.7.8 Filtering of Groundwater Samples

Filtering is an important process to remove suspended particulate that affect sample results. Filtration of groundwater samples is generally limited to metals analysis.

Filtering can be completed in the field using in-line filters or a vacuum filter kit. Filtering of samples can also be completed by the laboratory, in which case the samples must not be preserved and must be at the laboratory in at least 24 hours of sample collection.

7.8 Field Procedures for Residential Sampling

7.8.1 General

When sampling potable water supply wells it is important to ensure that the samples collected are representative of the aquifer being sampled. Poor or incorrect sampling techniques will result in erroneous sample results that can be disclosed to the public. Incorrect sample results may make any changes in the public perception hard to accomplish when correct results are reported.

7.8.2 Field Procedures

The requirements of a residential well sampling program should be reviewed with the Project Coordinator prior to initiating sampling activities. While similar field procedures used in groundwater sampling (including documentation, sample identification, date, time, etc.) are required in residential well sampling, additional procedures are also required.

Prior to collection of groundwater samples from a residential well, the well must be purged to ensure that samples collected are representative of the formation. Purging removes standing water from the well casing, pipes, and pressure or holding tank. Purging of a residential well requires the removal of one well volume. If access to the well is not available to determine the well volume, purging for a period of 15 to 30 minutes is generally sufficient. Field measurements for pH, conductivity, and temperature are recorded during purging activities until the readings indicate that stabilization has occurred.

Sampling of residential wells is generally performed using the existing pumping system. However, GHD purging and sampling equipment can be used. It is important that only designated **clean** purging and sampling equipment be used for residential well sampling. The use of the existing pumping system is preferred, as this is more representative of the water quality provided to the



residence. Using the existing pumping system also minimizes the possibility of damaging the well and existing pumping system when installing additional purging and sampling equipment.

If GHD equipment is used for residential well sampling, it must be cleaned prior to and between use with a bleach and deionized water solution wash followed by a thorough deionized water rinse.

Note: In addition to the special technical procedures noted, GHD personnel must be aware of this unique situation of conducting sampling at private residences. Special care must be taken to be polite and courteous at all times. Offer only necessary information and maintain a clean work area that is returned to pre-sampling conditions. Personnel should have proper identification available, and only remain in areas long enough to complete the required tasks.

Taps selected for residential well sampling should be located as close to the well as possible. Locate the taps before any treatment systems and, if possible, the pressure tank. It is important to note, if possible, all water treatment devices in operation at the residence including:

- Water softeners
- Filtration units
- Ultraviolet light
- Reverse osmosis
- Distillers
- Chlorinators

Leaking taps that allow water to flow from the stem of the valve handle and around the tap should not be used as sampling locations. Aerators, strainers, and hose attachments should be removed prior to sampling. Maintain a steady flow of water during sampling activities to avoid pressure fluctuations that may cause sheets of microbial growth lodged in the pipes to break loose. Open the cold water tap for a period of 15 to 30 minutes to allow for the complete purging of the pumping system. Maintain a smooth-flaring water stream at a low to moderate pressure without splashing. Do not change the flow rate. Changes in the flow could dislodge particles in the pipes or faucet.

When sampling for microbiological parameters, the end of the faucet must be flame sterilized. During residential well sample, never place caps from sample containers on the ground or in a pocket. Instead, hold the sample container in one hand and the sample container cap in the other. Be very careful not to touch the inside of the sample container cap. Wear new disposable gloves at each sampling location and following contact with a potential contaminant source. The inside of the sample bottle must not be touched with bare hands or allowed to contact the surface of the faucet.

7.8.3 Field Notes for Residential Sampling

Full documentation of each residential well is required and includes:

1. Well depth
2. Casing construction and diameter



3. Well installation date if known
4. Pumping system configuration
5. Piping system construction (e.g., copper, lead-joint, ABS)
6. Presence of treatment devices

Obtain the name and exact mailing address for all residence or well owners, as well as home and work telephone numbers. This information is required to inform the residence or well owner of the results of the sampling activities.

Document residential well sampling activities in a standard GHD field book. Figure 3.8 provides typical residential well sampling field note requirements. Note that additional documentation of well details, treatment devices, piping system, and special circumstances are required in the field book in addition to the sample log entry.

7.9 Field Procedures for Surface Water Sampling

7.9.1 General

Surface water sampling is performed to obtain samples for surface water bodies that are representative of existing surface water conditions.

Surface water sampling locations for surface water quality and groundwater interaction studies are selected based on the following:

1. Study objectives
2. Location of point surface discharges
3. Non-point source discharges and tributaries
4. Presence of structures (e.g., bridge, dam)
5. Accessibility

During surface water sampling it is important to obtain samples that are not impacted by the re-suspension of sediment produced because of improper or poor surface water sampling techniques.

7.9.2 Surface Water Sample Location Selection

Prior to conducting surface water sampling activities, the first requirement is the consideration and development of surface water sampling locations. It is important that all surface water sampling locations be selected in accordance with the Work Plan and described to and discussed with the Project Coordinator.

Bridges and piers are good locations for surface water sampling locations since they provide easy access and permit water sampling across the entire width of the surface water body. The JSA for sampling from bridges must include a traffic management plan to assure the employee has considered using a spotter, signage, cones, and flags to warn car traffic of the work adjacent to the



roadway. Wading for surface water samples increases the chances of disturbance of sediments from the floor of the surface water body.

When wading for surface water samples in lakes, ponds, streams, and slow moving rivers be aware of potential safety and health risks. A life vest and safety line must be worn at all times where footing is unstable or when sampling in fast moving or more than 3 feet (0.9 m) deep. A two-person team is required for most surface water sampling activities, a Project Manager must approve a one person sampling team. If the site conditions require the use of the life vest and safety line, the two people involved in the sampling must be competent swimmers.

Surface water samples must be collected with no suspended sediments. Surface water samples are collected commencing with the furthest downstream location to avoid sediment interference with upstream locations.

7.9.2.1 Rivers, Streams, and Creeks

Surface water samples are generally collected in areas of surface water bodies that are representative of the surface water body conditions. Representative surface water samples will usually be collected in sections of surface water bodies that have a uniform cross section and flow rate. Mixing is influenced by turbulence and water velocity, therefore the selection of surface water sampling locations immediately downstream of a riffle area (i.e., fast flow zone) will ensure good vertical mixing. These locations are also likely areas for deposition of sediment since this occurs in areas of decreased flow velocity.

Surface water sampling locations should not be established in areas near point source discharges including tributaries, industrial effluents, and municipal effluents. Surface water sampling of these source discharge points can be performed to assess the impact of these source areas on overall surface water quality.

Sample tributaries as close to the mouth as possible. It is important to select surface water sample locations considering the impact downstream, including tributary flow and sediment.

In all instances, properly document all surface water sampling locations in a standard GHD field book. Documentation may include photographs and tie-ins to known structures.

7.9.2.2 Lakes, Ponds, and Impoundments

The surface water in lakes, ponds, and impoundments has a greater tendency to be stratified than water in rivers and streams. Lack of mixing in these surface water bodies may require additional surface water sample collection. Extreme turbidity variances may occur where highly turbid surface water courses enter a lake or pond. Therefore, each layer of the stratified surface water column may need to be considered separately. Stratification is generally a result of water temperature differences, with cooler heavier water being trapped below warmer water.

Surface water sample locations for lakes, ponds, and impoundments should adequately represent the conditions of the surface water body. All intakes and outflows that may provide biased surface water representation should be identified and documented. Surface water sample locations with adjacent structures (e.g., banks, piers) may also provide biased samples, as the potential for boundary flow and eddies exists.



The number of surface water sample locations on lakes, ponds, or impoundments will vary depending on the purpose of the investigation, as well as the size and shape of the surface water body. In ponds and small impoundments a single surface water sample should be collected at the deepest point. In naturally formed ponds, the deepest point is usually near the center of the surface water body. In impoundments the point is usually near the dam.

In lakes and larger impoundments, several sub-samples should be taken to form a single composite sample. These vertical surface water sampling locations are collected along a pre-determined grid.

In irregular shaped lakes with several bays and covers that are protected from the wind, additional surface water samples are required to properly represent surface water quality at various locations in the lake. Additional surface water samples should be taken at discharges, tributaries, and other factors or sources that are suspected of affecting the surface water quality.

In all instances, properly document all surface water sampling locations in a standard GHD field book. Documentation may include photographs and tie-ins to known structures.

7.9.3 Sampling Equipment and Techniques

When collecting surface water samples, direct dipping of the sample container into the stream or water is acceptable unless the sample container contains preservatives. If preserved, a pre-cleaned unpreserved sample container should be used to collect the surface water sample. The surface water sample is then transferred to the appropriate preserved sample container. When collecting surface water samples, submerge the inverted bottle to the desired sample depth and tilt the opening of the sample container upstream to fill. During surface water sample collection, wading or movement may cause sediment deposits to be re-suspended and can result in biased samples. Wading is acceptable if the stream has a noticeable current and the samples are collected directly in the sample container when faced upstream. If the stream is too deep to wade in or if additional samples must be collected at various depths, additional sampling equipment will be required. Surface water samples should be collected about 6 inches (15 cm) below the surface, with the sample bottles being completely submerged. Taking the surface water sample at this depth eliminates the collection of floating debris in the sample container.

Surface water sample collection where the flow depth is less than 1 inch (<2.5 cm) requires the use of special equipment to eliminate sediment disturbance. Surface water sampling may be conducted with a container then transferred to the appropriate sample container, or collection may be performed using a peristaltic pump. A small excavation in the stream bed to create a sump for sample collection can also be considered but should be prepared in advance to allow all the sediment to settle prior to surface water sampling activities.

Teflon™ bailers can be used for surface water sampling if it is not necessary to collect surface water samples at specific depths. A bottom loading bailer with a check ball is sufficient. When the bailer is lowered through the water, the water is continually displaced through the bailer until the desired depth is reached. The bailer is retrieved and the check ball prohibits the release of the collected surface water sample. Bailers are not suitable in surface water bodies with strong currents, or where depth-specific sampling is required.



For discrete and specified depth surface water sampling, and the parameters to be monitored do not require a Teflon™ coated sampling device, a standard Kemmerer or Van Dorn sampler can be used. The Kemmerer sampler is a brass cylinder with rubber stoppers that leave the sampler ends open while the sampler is being lowered. The sampler is lowered in a vertical position to allow water to pass through. The Van Dorn sampler is plastic and is lowered in a horizontal position. For both samplers, a messenger is sent down a rope when the sampler has reached the required depth. The messenger causes the stopper on the sampler to close. The sampler is then retrieved and the surface water sample can be collected through a valve. DO sample bottles can be filled by allowing overflow using a rubber tube attached to the valve. During depth-specific surface water sampling, take care not to disturb bottom sediments.

Glass beakers or stainless steel cups may also be used to collect surface water samples if parameter interference does not occur. The beaker or cup must be rinsed at least three times with the surface water sample prior to sample collection.

All equipment must be thoroughly decontaminated as outlined in Section 7.6.

7.9.4 Field Notes for Surface Water Sampling

Use a standard GHD field book to record daily surface sampling activities, describe surface water sampling locations, sampling techniques, and, if applicable, provide a description of photographs taken. Visual observations are important and provide valuable information when interpreting surface water quality results. Observations include:

1. Weather conditions
2. Stream flow directions
3. Stream physical conditions (width, depth, etc.)
4. Tributaries
5. Effluent discharges
6. Impoundments
7. Bridges
8. Railway trestles
9. Oil sheens
10. Odors
11. Buried debris
12. Vegetation
13. Algae
14. Fish and other aquatic life
15. Surrounding industrial areas



The following factors should be considered for surface water sampling:

1. **Predominant Surrounding Land Use:** Observe the prevalent land use type in the vicinity and note any other land uses in the area which, although not dominant, may potentially affect surface water quality.
2. **Local Watershed Erosion:** Note the existing or potential erosion of soil in the local watershed and its movement into the stream. Erosion can be rated through visual observation of watershed stream characteristics including increases or decreases in turbidity.
3. **Local Watershed Non-Point Source Pollution:** This refers to problems or potential problems other than erosion and sedimentation. Nonpoint source pollution can be diffuse agricultural and urban runoff. Other factors may include feed lots, wetlands, septic systems, dams, impoundments, and mine seepage.
4. **Estimated Stream Width:** The estimated distance from shore at a transect representative of the stream width in the area.
5. **Estimated Stream Depth:** Riffle (rocky area), run (steady flow area), and pool (still area). Estimate the vertical distance from the water surface to the bottom of the surface water body at a representative depth at three locations.
6. **High Water Mark:** Estimate the vertical distance from the bank of the surface water body to the peak overflow level, as indicated by debris hanging in bank or flood plain vegetation, and deposition of silt. In instances where bank flow is rare, high water marks may not be evident.
7. **Velocity:** Record or measure the stream velocity in a representative run area.
8. **Dam Present:** Indicate the presence or absence of a dam upstream or downstream of the surface water sampling location. If a dam is present, include specific information detailing the alteration of the surface water flow.
9. **Channelized:** Indicate if the area surrounding the surface water sampling location is channelized.
10. **Canopy Cover:** Note the general proportion of open to shaded areas which best describes the amount of cover at the surface water sampling location.

7.10 Follow-Up Activities

The following should be performed once groundwater, residential, and surface water sampling is completed:

1. Double check the Work Plan and QAPP to ensure all samples and QA/QC samples have been collected and confirm with the Project Coordinator.
2. Decontaminate all equipment at the site then return clean to the appropriate office equipment manager.
3. Dispose of purge water and cleaning fluid as specified in the Work Plan.
4. Notify the contract laboratory when the samples should arrive. Enclose a completed chain-of-custody in each cooler.



5. Complete and file the appropriate forms and data sheets. Also file the field notes. For groundwater, residential, and surface water sampling these forms include:
 - Project Planning, Completion, and Follow-Up Checklist (Form SP-02)
 - Well Development, Purging, and Sampling Form (Form SP-06)
 - Sample Collection Data Sheet - Groundwater Sampling Program (Form SP-08)
 - Monitoring Well Record for Low-Flow Purging (if performed) (Form SP-09)
6. Return site and well keys.

7.11 References

For additional information pertaining to groundwater sampling activities the user of this manual may reference the following:

ASTM D5474	Guide for Selection of Data Elements for Groundwater Investigations
ASTM D4696	Guide for Pore-Liquid Sampling from the Vadose Zone
ASTM D5979	Guide for Conceptualization and Characterization of Groundwater Systems
ASTM D5903	Guide for Planning and Preparing for a Groundwater Sampling Event
ASTM D4448	Standard Guide for Sampling Groundwater Wells
ASTM D6001	Standard Guide for Direct-Push Water Sampling for Geoenvironmental Investigations.

For additional information pertaining to surface water sampling, the user of this manual may reference the following:

ASTM D5358	Practice for Sampling with a Dipper or Pond Sampler
ASTM D4489	Practices for Sampling of Waterborne Oils
ASTM D3325	Practice for the Preservation of Waterborne Oil Samples
ASTM D4841	Practice for Estimation of Holding Time for Water Samples Containing Organic and Inorganic Constituents
ASTM D4411	Guide for Sampling Fluvial Sediment in Motion
ASTM D4823	Guide for Core-Sampling Submerged, Unconsolidated Sediments
ASTM D3213	Practice for Handling, Storing, and Preparing Soft Undisturbed Marine Soil
ASTM D3976	Practice for Preparation of Sediment Samples for Chemical Analysis
ASTM E1391	Guide for Collection, Storage, Characterization, and Manipulation of Sediments for Toxicological Testing
ASTM D4581	Guide for Measurement of Morphologic Characteristics of Surface Water Bodies
ASTM D5906	Guide for Measuring Horizontal Positioning During Measurements of Surface Water Depths
ASTM D5073	Practice for Depth Measurement of Surface Water

Attachment D PFC Sampling Checklist

PFCs Sampling Checklist

Date: _____

Weather (*temp./precipitation*): _____ Site Name: _____

Field Clothing and PPE:

- No clothing or boots containing Gore-Tex™
- All safety boots made from polyurethane and PVC
- No materials containing Tyvek®
- Field crew has not used fabric softener on clothing
- Field crew has not used cosmetics, moisturizers, hand cream, or other related products this morning
- Field crew has not applied unauthorized sunscreen or insect repellent

Field Equipment:

- No Teflon® or LDPE containing materials on-site
- All sample materials made from stainless steel, HDPE, acetate, silicon, or polypropylene
- No waterproof field books on-site
- No plastic clipboards, binders, or spiral hard cover notebooks on-site
- No adhesives (Post-It Notes) on-site

- Coolers filled with regular ice only. No chemical (blue) ice packs in possession

Sample Containers:

- All sample containers made of HDPE or polypropylene
- Caps are unlined and made of HDPE or polypropylene

Wet Weather (as applicable):

- Wet weather gear made of polyurethane and PVC only

Equipment Decontamination:

- "PFC-free" water on-site for decontamination of sample equipment. No other water sources to be used.
- Alconox and Liquinox to be used as decontamination materials

Food Considerations:

- No food or drink on-site with exception of bottled water and/or hydration drinks (i.e., Gatorade and Powerade) that is available for consumption only in the staging area

If any applicable boxes cannot be checked, the Field Lead shall describe the noncompliance issues below and work with field personnel to address noncompliance issues prior to commencement of that day's work. Corrective action shall include removal of noncompliance items from the site or removal of worker offsite until in compliance.

Describe the noncompliance issues (include personnel not in compliance) and action/outcome of noncompliance:

Field Lead Name: _____

Field Lead Signature: _____ Time: _____

PFC Sampling – Prohibited and Acceptable Items

Prohibited	Acceptable
Field Equipment	
Teflon® containing materials	High-density polyethylene (HDPE) materials
Low density polyethylene (LDPE) materials	Acetate Liners
	Silicon Tubing
Waterproof field books	Loose paper (non-waterproof)
Plastic clipboards, binders, or spiral hard cover notebooks	Aluminum field clipboards or with Masonite
	Sharpies®, pens
Post-It Notes®	
Chemical (blue) ice packs	Regular ice
Field Clothing and PPE	
New cotton clothing or synthetic water resistant, waterproof, or stain-treated clothing, clothing containing Gore-Tex™	Well-laundered clothing made of natural fibers (preferable cotton)
Clothing laundered using fabric softener	No fabric softener
Boots containing Gore-Tex™	Boots made with polyurethane and PVC
Tyvek®	Cotton clothing
No cosmetics, moisturizers, hand cream, or other related products as part of personal cleaning/showering routine on the morning of sampling	<p>Sunscreens - Alba Organics Natural Sunscreen, Yes To Cucumbers, Aubrey Organics, Jason Natural Sun Block, Kiss my face, Baby sunscreens that are “free” or “natural”</p> <p>Insect Repellents - Jason Natural Quit Bugging Me, Repel Lemon Eucalyptus Insect repellent, Herbal Armor, California Baby Natural Bug Spray, BabyGanics</p> <p>Sunscreen and insect repellent - Avon Skin So Soft Bug Guard Plus – SPF 30 Lotion</p>
Sample Containers	
LDPE or glass containers	HDPE or polypropylene
Teflon-lined caps	Unlined polypropylene caps
Rain Events	
Waterproof or resistant rain gear	Gazebo tent that is only touched or moved prior to and following sampling activities
Equipment Decontamination	
Decon 90®	Alconox® and/or Liquinox®
Water from an on-site well	Potable water from municipal drinking water supply
Food Considerations	
All food and drink, with exceptions noted on right	Bottled water and hydration fluids (i.e, Gatorade® and Powerade®) to be brought and consumed only in the staging areas