



RICK SNYDER
GOVERNOR

STATE OF MICHIGAN
DEPARTMENT OF ENVIRONMENTAL QUALITY
LANSING DISTRICT OFFICE



DAN WYANT
DIRECTOR

August 11, 2015

Mr. Dave Favero
RACER Trust
500 Woodward Avenue, Suite 1510
Detroit, Michigan 48226

Dear Mr. Favero:

SUBJECT: Davison Road Industrial Land Remediation Summary,
Burton, Genesee County, Michigan; Facility ID No.: 25000447

The Department of Environmental Quality (DEQ), Remediation and Redevelopment Division, has reviewed the Remediation Summary for the Davison Road Industrial Land and concurs with the summary. The Expected Future Site Requirements are correct using the information we have. Additional information may slightly alter these requirements.

The DEQ continues to support RACER's efforts to address the environmental risks at this Facility in anticipation of site redevelopment. If I can be of any further assistance in this matter, please do not hesitate to contact me.

Sincerely,

James E. Innes
Lansing District Office
Remediation and Redevelopment Division
517-284-5115
innesj@michigan.gov

cc: Mr. Dennis Eagle, DEQ



RACER DAVISON ROAD INDUSTRIAL LAND REMEDICATION SUMMARY

August 11, 2015

INTRODUCTION

RACER's practice is to work with buyers to find mutually acceptable solutions for site development and remediation requirements. This brief Remediation Summary is designed to provide the following information about the Davison Road Industrial Land (Site) to assist potential buyers:

- Site history and description
- Previous Site investigations
- Current Site status
- Expected future Site requirements

Full background reports are available and can be provided if requested. In addition, more specific and detailed discussions can be arranged with RACER and the Michigan Department of Environmental Quality (MDEQ) at an appropriate time once a draft conceptual Site development plan has been prepared. The MDEQ supports the common goals of Site remediation and development and, in cooperation with RACER, will streamline and expedite remediation consistent with MDEQ regulatory requirements.

SITE HISTORY AND DESCRIPTION

Located off Davison Road, this 56.21-acre vacant parcel is bordered by:

- Davison Road and mixed commercial properties to the north;
- Canadian National railroad line to the south;
- A Consumer's Power Company right-of-way and a General Motors Customer Care and Aftersales warehouse and distribution facility to the west; and
- A vacant parcel to the east.
- Gilkey Creek crosses the southwest portion of the Site.

See Figure 1 and 2, and Appendix 1.

Based on review of historical aerial photographs and other records it appears that the Site was:

- Agriculture land until the late 1950s;
- Limited residential development began in the late 1950s and early 1960s;
- Purchased by the former General Motors Corporation (GMC) in the early 1960s; and
- Associated with the Delphi Energy and Engine Management Systems Flint East Facility (the former Delphi Facility on Center Road west of the Site), until 1999, when Delphi Automotive Systems was divested from GMC.

In the 1970s GMC placed fill on a portion of the Site. The fill included construction debris, miscellaneous inert solid waste and foundry sand primarily from the former GMC Buick Motor Division facility in Flint, MI. The fill is located primarily in the central and southeast portion of the property and, where present, is generally less than five feet thick but can be as much as 13 feet thick in isolated locations. This fill material was the only concern identified for the Site in a Phase I Environmental Assessment (ESA) completed for the Site in 1995.

The remainder of the Site was never used by GMC, with the exception of an asphalt test track that extends through the northern portion of the Site and onto the adjoining parcel to the east. No manufacturing activities took place at this Site. A portion of the Site lies in the floodway and some adjacent ground lies within the 100 year floodplain. In addition, a small portion of the southeast part of the Site is included in the National Wetlands Survey.

PREVIOUS SITE INVESTIGATIONS

Site investigations were completed by GMC from 1996 through November 2007. The investigations included soil and groundwater characterization, fill delineation, and ecological habitat assessment. RACER completed additional Site Investigations from 2012 through the present.

Two primary environmental concerns related to this historic fill were identified – one ecological based issue associated with groundwater migrating to surface water (so – called Groundwater/Surface Water Interface (GSI) Protection Criteria and two limited areas where several soil samples contained concentrations of polynuclear aromatic hydrocarbons (PNAs) above the MDEQ Part 201 Non Residential Direct Contact Protection Criteria (Figure 3). Both issues can be addressed by RACER with little to no impact on future redevelopment of the Site.

No geotechnical soil testing has been conducted at the Site, however a cross-section key and cross-sections illustrating the subsurface material at the Site are included in Figures 4 and 5, and select soil boring information is included in Appendix 2. Subsurface material (some of which is fill) generally consists of sand or silt/clay over a saturated sand/silt underlain by clay. Site investigations delineated the area containing fill material.

A figure illustrating GSI groundwater compliance monitoring locations with concentrations of certain metals above MDEQ Non-residential Part 201 GSI Cleanup Criteria (Figure 2). Depth to groundwater is generally five to fifteen feet below grade.

Overall the identified exceedances of MDEQ Part 201 criteria are relatively minor, and with implementation of appropriate institutional controls and due care, these limited exceedances will not result in human exposures nor pose any risks to human health.

CURRENT SITE STATUS

Remediation activities are currently being conducted by Environmental Resources Group LLC (ERG) on behalf of RACER, with approval and oversight by the MDEQ. The RACER Trust Settlement Agreement allocated \$612,280 for Site remediation, with approximately \$350,000 currently remaining.

An additional round of groundwater monitoring has recently been completed to support a Request to MDEQ for a Mixing Zone Based GSI Criteria for arsenic concentrations in the groundwater located in monitoring wells located near the Gilkey Creek. MDEQ has concurred that the other metals identified in groundwater do not pose a threat due to the distance from the creek.

Additional investigation is necessary to verify the presence or absence of soil impacts identified in historical Site investigations above MDEQ Non-Residential Direct Contact Criteria at two locations illustrated on Figure 2.

EXPECTED FUTURE SITE REQUIREMENTS

A No Further Action (NFA) determination or Certificate of Completion (COC) issued by MDEQ is expected for the Site based on

- MDEQ approving an acceptable Mixing Zone Based GSI criteria for arsenic;
- Filing of a Declaration of Restrictive Covenant (DRC) to be recorded with the Genesee County Register of Deeds; and
- Appropriate action to address any soil with exceedances of MDEQ Non-Residential Direct Contact Criteria (deed restriction or excavation and off-site disposal).

Results of the additional investigation to verify the presence or absence of soil impacts identified in historical Site investigations above MDEQ Non-Residential Direct Contact Criteria will be used to define any necessary final corrective measures which may include excavation and disposal. The schedule for this work can be coordinated with Site development to ensure Site development schedules are not delayed.

Follow-up groundwater monitoring primarily using existing monitoring wells near Gilkey Creek, may be necessary for a year or more to verify that concentrations of arsenic in the groundwater near the Creek remain stable and below the Mixing Zone Based GSI criteria. Groundwater monitoring is expected to be necessary quarterly or less often.

Upon MDEQ approval of the NFA request or issuance of a COC, it is anticipated that Site remediation activities will be limited to groundwater monitoring and ultimately, abandonment of monitoring wells.

The above activities can be coordinated to ensure no adverse impact on Site development activities.

Attachments

Figure 1 - Site Location Map

Figure 2 –Site Map


Figure 3 – Soil and Groundwater Exceedance Map

Figure 4 - Cross Section A-A'

Figure 5 – Cross Section B-B'

Appendix 1 – Site Boundary and Topographic Surveys

Appendix 2 – Soil Information



LOCATION MAP




FIGURE
1


DRWG. by : MA
CHECK :
DATE : 8/11/2015
DWG: 2015 Aug Fig 1-2
SHEET : 1 of 4

CONT. INT.: N/A
FIELD : MD/SM/LB
V. SCALE : N/A
SCALE: 1"=200'
JOB#: 12-068




SITE LOCATION MAP
RACER TRUST
DAVISON ROAD INDUSTRIAL LAND- BURTON, MICHIGAN



ERG Environmental Resources Group
28003 Center Oaks Court • Suite 106 • Wixom, MI • 48393
Phone: 248-773-7986 • Fax: 248-924-3108



FILED:\Projects\2012\12-068 Burton, MI RACER Trust\DWG\SURV\12-068-2015-Map Fig 1-2.dwg DATE: 11/1/2015 5:29 AM



NOTE

ALL SOIL BORINGS CONTAIN CONCENTRATIONS OF METALS, VOCs AND/OR PNAs ABOVE THE PART 201 CALCULATED FACILITY SPECIFIC GSI PROTECTION CRITERIA

FIGURE 3

DRWG. by : MA
CHECK :
DATE : 8/11/2015
DWG: 2015 Aug Fig 1-2
SHEET : 3 of 5

CONT. INT.: N/A
FIELD : MD/SM/LB
V. SCALE : N/A
SCALE: 1"=200'
JOB# : 12-068


SOIL & GROUND WATER EXCEEDANCE MAP

RACER TRUST
DAVISON ROAD INDUSTRIAL LAND- BURTON, MICHIGAN

PREPARED BY:

ERG Environmental Resources Group
28003 Center Oaks Court • Suite 106 • Wixom, MI • 48393
Phone: 248-773-7986 • Fax: 248-924-3108


LEGEND




FILL



SILT/CLAY





SILT/SAND



CLAY

2 }
4 } BLOW COUNTS TAKEN
4 } AT TIME OF DRILLING
5 }



FIGURE

4



Environmental Resources Group

28003 Center Oaks Court • Suite 106 • Wixom, MI • 48393
Phone: 248-773-7986 • Fax: 248-924-3108

RACER TRUST

DAVISON ROAD INDUSTRIAL LAND


CROSS SECTION (A-A')

JOB No. 12-068

DR. BY: MA DATE: 8/11/2015

SHEET: 4 OF 5

SCALE: 1" = 200'



FIGURE

5



Environmental Resources Group
 28003 Center Oaks Court • Suite 106 • Wixom, MI • 48393
 Phone: 248-773-7986 • Fax: 248-924-3108

RACER TRUST


DAVISON ROAD INDUSTRIAL LAND

CROSS SECTION (B-B')


JOB No. 12-068

DR. BY: MA DATE: 8/11/2015

SHEET: 5 OF 5



LEGEND




FILL



SILT/CLAY



SILT/SAND




CLAY

2
4
4
5 } BLOW COUNTS TAKEN AT TIME OF DRILLING


APPENDIX 1

SITE BOUNDARY AND TOPOGRAPHIC SURVEY


BOUNDARY SURVEY
MONITORING WELL MAP



LOCATON MAP



EXISTING LEGEND



LEGAL DESCRIPTION

Legal Description

A part of the N 1/2 of Section 10, T7N-R7E, City of Burton, Genesee County, Michigan more particularly described as beginning at the N 1/4 corner of said Section 10, thence S00°28'55" E, 300.00 feet; thence S88°05'10" W, 30.00 feet; thence S00°28'55", 556.34 feet; thence East, 74.53 feet; thence South, 240.00 feet; thence W10°, 72.51 feet; thence S00°28'55", 907.74 feet; thence S65°16'21", 311.57 feet; thence S50°50'34" W, 360.47 feet; thence N89°15'08" W, 906.17 feet; thence N00°22'32" W, 464.18 feet; thence S89°37'28" W, 72.12 feet; thence N00°22'43" W, 132.83 feet; thence S89°18'22" W, 206.67 feet; thence along the arc of a curve to the left 147.58 feet, said curve has a radius of 153.80 feet, a central angle of 54°58'39" and a long chord which bears N39°38'31" W, 141.98 feet; thence along the arc of a curve to the right 109.34 feet, said curve has a radius of 93.80 feet, a central angle of 66°47'07" and a long chord which bears N33°44'17" W, 103.25 feet; thence S88°02'45" E, 763.74 feet; thence S00°15°59" E, 109.87 feet; thence S88°02'45" E, 433.71 feet; thence N00°28'55" W, 660.00 feet; thence along the North line of Section 10 and Centerline of Davison Road, S88°02'44", 66.00 feet to the Point of Beginning, containing 55.630 acres and subject to the rights of the public over Davison Road, also subject to any other easements or restrictions of record.

Sections corner Witnesses

N 1/4 corner Section 10, H-03
Found Remonumentation cap, per the position as described and recorded in LCRC, L.4587, P.423 Genesee
County Records.

NW corner Section 20, G-03
Found Remonumentation cap, per the position as described and recorded in LCRC, L.4587, P.423 Genesee
County Records.

W 1/4 corner Section 10, G-04
Found Remonumentation cap, per the position as described and recorded in LCRC, L.1881, P.880 Genesee
County Records.

E 1/4 corner Section 10, I-04
Found Remonumentation cap, per the position as described and recorded in LCRC, L.2081, P.591 Genesee
County Records.

FLOODPLAIN INFORMATION

FEMA FIRM MAP NO: 26049C0194D
EFFECTIVE DATE: SEPT. 25, 2009




ZONE X:
AREAS DETERMINED TO BE OUTSIDE OF THE 0.2% ANNUAL CHANCE FLOODPLAIN.

ZONE AE:
BASE FLOOD ELEVATIONS DETERMINED

BASE FLOOD ELEV.: 757'

BENCHMARKS

DATUM: NAVD 88

-  **BENCHMARK A:** ELEV = 761.60
 Set Nail and Tag in W/side 14" cottonwood. Approximately 155' E and 65' S of MW-10-12.
-  **BENCHMARK B:** ELEV = 760.19
 N rim of existing Sanitary MH. Approximately 140' N and 65' W of MW-04.
-  **BENCHMARK C:** ELEV = 738.71
 NGS BM NO. 25609

BURTON SITE

Prepared for
**MONUMENT ENGINEERING
GROUP ASSOCIATES**

Date of Photography NOVEMBER 22, 2012		Scale 1" = 50'	C.I. 1'
Compiled by CES	Edited by CJB	Checked by CJB	Sheet



NOTE: DENSE TREE AREAS AND EVERGREEN AREAS INDICATE WHERE THE GROUND IS OBSCURED AND THE ACCURACY OF THE CONTOURS MAY NOT BE RELIABLE. IT IS RECOMMENDED THAT A FIELD CHECK BE MADE WITHIN THESE AREAS BEFORE ANY DESIGN OR WORK IS PERFORMED.




4515 GLENBROOK RD.
WILLOUGHBY, OHIO 44094
WWW.AEROCON.COM
SKYMAP@AEROCON.COM
(440) 946-0277
Aerocon Photogrammetric Services, Inc.

APS
Project #
12087

TOPOGRAPHIC SURVEY




EXISTING LEGEND



- DECIDUOUS TREE, CONIFEROUS TREE, SHRUB
- TREE LINE/ CANOPY
- UG TELE, MH, TELE PED, CABLE PED
- UG FIBER, PED, LINE MARKER
- UG ELEC, MH, TRANSFORMER, AC UNIT, METER
- OH ELEC, UTIL POLE, GUY WIRE
- GROUND LIGHT, POLE, POLE W/ ARM LT
- LIGHT MH, LT CTRL BOX, PH. BOOTH, PARK, METER
- ELEC HAND HOLE, OUTLET, SIGNAL MH, SIGNAL BOX
- UG GAS, MH, VALVE, LINE MARKER
- GAS WELL, METER, VENT
- WATER MAIN, MH, VALVE IN BOX, HYDRANT
- WATER WELL, METER, STOP BOX, POST INDICATOR VALVE
- IRRIGATION CONTROL VALVE, SPRINKLER HEAD
- STORM SEWER, MH, CB, INLET, YARD DRAIN
- CULVERT/ END SECTION
- SANITARY SEWER, MH, CLEAN OUT
- COMBINED SEWER, MH
- STEAM LINE, MH
- MISC. MANHOLE, HAND HOLE, HAND BOX
- SIGN, FLAG POLE, GUARD POST, ROCK
- SECTION LINE, SECTION CORNER
- SURVEY CONTROL POINT, BENCHMARK
- FOUND IRON ROD (FIR), FD MON, FD PK
- SET IRON ROD (SIR), SET PK, MAG NAIL
- SPOT ELEVATION
- CONTOUR
- FENCE
- GUARD RAIL
- RAILROAD SIGNAL, SIGNAL BOX
- ROW MARKER
- SOIL BORING
- ASPHALT
- CONCRETE

ENGINEERS - SURVEYORS - CONSULTANTS - LANDSCAPE
ARCHITECTS - LAND PLANNERS
638 SOUTH GRAND AVE.
FOWLERVILLE
MICHIGAN 48846
(OFFICE) 517-223-9512
(FAX) 517-223-9587
Copyright © 2012, MEGA, INC.



Monument Engineering Group Associates, Inc.


CLIENT :
WILCOX

TOPOGRAPHIC SURVEY

PART OF N 1/2, SECTION 10, T7N-R7E
CITY OF BURTON, GENESEE COUNTY
MICHIGAN

REVISIONS	DATE

CONT. INT.: N/A
FIELD : MD/SM/LB
V. SCALE :
SCALE: 1"=150'
JOB#: 12-068
DRWG. by : MA
CHECK : AP
DATE : 09/18/2012
12-068Bnd
SHEET : 2 OF 2



2

APPENDIX 2

SOIL INFORMATION



5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

SOIL BORING LOG

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-21-12

BORING LOCATION: Near fence on east central part of site

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/17/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Graves

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 2.0) Brown, Dry, SILT; with fine sand and coarse sand			1SS 0-1'			<1	Collected sample at 0-2'
					2SS 1-2'			<1	
		(2.0 - 6.0) Hard, Brown, Dry, SILT; with clay and fine sand, trace coarse sand			3SS 2-3'			<1	
					4SS 3-4'			<1	
					5SS 4-5'			<1	
-5.0	5				6SS 5-6'			<1	
		(6.0 - 7.5) Brown, Moist to Wet, Fine SAND			7SS 6-7'			<1	Collected sample at 6-6.5'
		(7.5 - 8.0) Hard, Brown, Dry, CLAY			8SS 7-8'			<1	
		(8.0 - 13.5) Hard, Gray, Dry, CLAY			9SS 8-9'			<1	
					10SS 9-10'			<1	
-10.0	10				11SS 10-11'			<1	
					12SS 11-12'			<1	
					13SS 12-13'			<1	
					14SS 13-14'			<1	
		(13.5 - 14.5) Gray, Moist, Fine SAND			15SS 14-15'			<1	
-15.0	15	(14.5 - 15.5) Gray, Moist, Silty Fine SAND			16SS 15-16'			<1	
		(15.5 - 16.0) Gray, Moist, Fine SAND							

GROUNDWATER OBSERVATIONS

⚡ DURING DRILLING: 6.5'

⚡ AT COMPLETION OF DRILLING: NR

⚡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-22-12

BORING LOCATION:

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/17/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Graves

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 3.0) Brown, Dry, SILT and SAND; with gravel			1SS 0-1'			<1	
					2SS 1-2'			<1	
					3SS 2-3'			<1	Collected sample at 2-3'
		(3.0 - 6.5) Brown, Dry, SILT and CLAY; with coarse sand			4SS 3-4'			<1	
					5SS 4-5'			<1	
-5.0	5				6SS 5-6'			<1	
		(6.5 - 7.5) Brown, Wet, Fine SAND			7SS 6-7'			<1	
		(7.5 - 14.0) Hard, Gray, Dry, CLAY			8SS 7-8'			<1	
					9SS 8-9'			<1	
-10.0	10				10SS 9-10'			<1	
					11SS 10-11'			<1	
					12SS 11-12'			<1	
					13SS 12-13'			<1	
					14SS 13-14'			<1	
-15.0	15	(14.0 - 16.0) Brown, Moist, Fine SAND			15SS 14-15'			<1	
					16SS 15-16'			<1	

GROUNDWATER OBSERVATIONS

≡ DURING DRILLING: 7'

☛ AT COMPLETION OF DRILLING: NR

≡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-23-12

BORING LOCATION:

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/17/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Graves

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 7.0) Brown, Dry, SILT and SAND; with concrete pieces			1SS 0-1'			<1	
		Obstruction at 1'			2SS 1-2'			<1	
					3SS 2-3'			<1	
					4SS 3-4'			<1	
					5SS 4-5'			<1	
-5.0	5				6SS 5-6'			<1	
					7SS 6-7'			<1	
		(7.0 - 9.0) Hard, Dry, Brown, SILT and CLAY; with coarse sand			8SS 7-8'			<1	
		(9.0 - 9.5) Brown, Moist, Fine SAND and SILT			9SS 8-9'			<1	
-10.0	10	(9.5 - 10.0) Brown, Wet, Fine SAND and SILT			10SS 9-10'			<1	
		(10.0 - 13.0) Gray, Moist, SILT			11SS 10-11'			<1	
					12SS 11-12'			<1	
					13SS 12-13'			<1	
		(13.0 - 16.0) Gray, Moist, CLAY			14SS 13-14'			<1	
-15.0	15				15SS 14-15'			<1	
					16SS 15-16'			<1	

Collected sample
at 1.5-2.5'

GROUNDWATER OBSERVATIONS

≡ DURING DRILLING: 9.5'

▼ AT COMPLETION OF DRILLING: NR

≡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-24-12

BORING LOCATION: Near MW-2

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/16/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Lambert

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 2.0) Dark Brown, Dry, Foundry FILL; with silt and organics, some gravel			1SS 0-1'			<1	
					2SS 1-2'			1.9	
		(2.0 - 4.0) Dark Brown-Black, Dry, Foundry FILL; with silt and organics, some gravel			3SS 2-3'			<1	
		(4.0 - 4.5) Gray, Moist, CLAY; with silt, trace gravel			4SS 3-4'			12.9	Collected sample at 3-4'
		(4.5 - 12.0) Gray/Brown, Moist, SILT; trace clay and gravel			5SS 4-5'			1	
-5.0	5				6SS 5-6'			<1	
					7SS 6-7'			<1	
		Evidence of foundry debris from 7.5-12'			8SS 7-8'			<1	
					9SS 8-9'			<1	
					10SS 9-10'			<1	
-10.0	10				11SS 10-11'			<1	
					12SS 11-12'			<1	
		(12.0 - 16.0) No recovery - was unable to collect a sample.			13SS 12-13'			<1	
-15.0	15								

GROUNDWATER OBSERVATIONS

∞ DURING DRILLING: NE
 ▼ AT COMPLETION OF DRILLING: NR
 ∞ AFTER NR HOURS: NR
 NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR
 AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index
 *St = Hand Torvane Shear Strength
 *Qp = Pocket Penetrometer
 *Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-25-12

BORING LOCATION: Near MW-2

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/16/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Graves

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 2.5) Brown, Dry, SAND and SILT; trace gravel			1SS 0-1'			<1	
					2SS 1-2'			<1	
					3SS 2-3'			<1	
		(2.5 - 5.0) Dark Brown, Dry, Fine SAND and SILT; with concrete pieces			4SS 3-4'			<1	
		Driller reported rocks/concrete from 3-5'			5SS 4-5'			<1	
-5.0	5	(5.0 - 12.0) Black, Dry, SILT and SAND; trace foundry sand, concrete and debris			6SS 5-6'			<1	
					7SS 6-7'			<1	
					8SS 7-8'			<1	
		Driller reported concrete at 8.5'			9SS 8-9'			<1	
					10SS 9-10'			<1	
-10.0	10	White pasty clay material with slight odor encountered from 11-11.5'			11SS 10-11'			<1	
					12SS 11-12'			<1	Collected sample at 11-12'
		(12.0 - 15.0) Gray, CLAY; with silt			13SS 12-13'			<1	
					14SS 13-14'			<1	
					15SS 14-15'			<1	
-15.0	15	(15.0 - 16.0) Gray, Wet, Fine SAND			16SS 15-16'			<1	

GROUNDWATER OBSERVATIONS

≡ DURING DRILLING: 15.5'

☛ AT COMPLETION OF DRILLING: NR

≡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-26-12

BORING LOCATION: Near MW-2

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/16/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Graves

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 2.5) Brown, Dry, Sandy SILT; trace gravel			1SS 0-1'			<1	
					2SS 1-2'			<1	
					3SS 2-3'			<1	
		(2.5 - 5.0) Dark Brown, Dry, Fine SAND and SILT; trace broken glass and gravel			4SS 3-4'			<1	
					5SS 4-5'			<1	
-5.0	5	(5.0 - 10.0) Black, Moist, SILT and SAND; trace foundry sand			6SS 5-6'			<1	
					7SS 6-7'			12	
					8SS 7-8'			19	Collected sample at 7-8'
					9SS 8-9'			1	
					10SS 9-10'			1	
-10.0	10	(10.0 - 13.0) Gray, Moist, SILT and CLAY; trace coarse sand			11SS 10-11'			1	
					12SS 11-12'			1	
					13SS 12-13'			1	
		(13.0 - 16.0) Gray, Wet, Fine SAND becoming more coarse with depth			14SS 13-14'			<1	
					15SS 14-15'			<1	
-15.0	15				16SS 15-16'			<1	

GROUNDWATER OBSERVATIONS

≡ DURING DRILLING: 13.5'

☞ AT COMPLETION OF DRILLING: NR

≡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-27-12

BORING LOCATION: West of SB-28, north of MW-13

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/20/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Lambert

CITY: Burton **COUNTY:** Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 4.0) Brown, Dry becoming Moist, Sand and Silt FILL; some organics, cobbles, slag, and concrete pieces			1SS 0-1'			<1	
					2SS 1-2'			<1	
					3SS 2-3'			<1	Collected sample at 2-3'
					4SS 3-4'			<1	
		(4.0 - 6.0) Moist, Sand and Silt FILL; some cobbles and slag			5SS 4-5'			<1	
-5.0	5				6SS 5-6'			<1	
		(6.0 - 8.0) Dark Brown Mottled Red, Moist, Clayey SILT; some slag, cobbles and wood debris			7SS 6-7'			<1	Collected sample at 6-7'
					8SS 7-8'			<1	
		(8.0 - 11.0) Gray, Wet, Sandy SILT; trace gravel			9SS 8-9'			<1	
-10.0	10				10SS 9-10'			<1	
					11SS 10-11'			<1	
		(11.0 - 15.8) Gray, Wet, SILT; some sand			12SS 11-12'			<1	
					13SS 12-13'			<1	
					14SS 13-14'			<1	
					15SS 14-15'			<1	
-15.0	15	(15.8 - 16.0) Gray, Moist, CLAY			16SS 15-16'			<1	

GROUNDWATER OBSERVATIONS

≡ DURING DRILLING: 8.5'

▼ AT COMPLETION OF DRILLING: NR

≡ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine



SOIL BORING LOG

5859 Sherman Road
Saginaw, MI 48604
989-752-6500
989-752-6600 fax

PROJECT: Davison Road Industrial Landfill

CLIENT: Racer Trust

BORING NO: SB-28-12

BORING LOCATION: Far east soil boring, north of MW-14

METHOD OF DRILLING: Auger

GROUND ELEVATION: NR

NOTES:

DATE DRILLED: 07/19/12

JOB NUMBER: 10496.00004

DRILLER/HELPER: Ludwick/MacMurray

DRILL RIG: AMS

LOGGED BY: Lambert

CITY: Burton

COUNTY: Genesee

Elevation	Depth (ft)	Material Description	Soil Type	Water Level	Sample #/Type Sample Depth SPT Results (N-Value) % REC.	Moisture %	Unconfined Comp. Strength* (tsf)	PID (ppm)	Analytical Parameters
0.0	0	(0.0 - 2.0) Brown, Dry, SAND and SILT; trace plastic debris and concrete			1SS 0-1'			<1	
					2SS 1-2'			<1	
		(2.0 - 4.0) Brown, Dry, SILT and SAND; trace gravel			3SS 2-3'			<1	Collected sample at 2-3'
					4SS 3-4'			<1	
		(4.0 - 6.0) Brown, Moist, SILT and SAND; trace organics and cobbles			5SS 4-5'			<1	
-5.0	5				6SS 5-6'			<1	
		(6.0 - 8.0) Brown/Orange, Moist, Fine to Medium SAND			7SS 6-7'			<1	Collected sample at 6-7'
					8SS 7-8'			<1	
		(8.0 - 10.5) Brown, Wet, SILT			9SS 8-9'			<1	
					10SS 9-10'			<1	
-10.0	10				11SS 10-11'			<1	
		(10.5 - 15.0) Gray, Wet, Silty CLAY			12SS 11-12'			<1	
					13SS 12-13'			<1	
					14SS 13-14'			<1	
					15SS 14-15'			<1	
-15.0	15				16SS 15-16'			<1	
		(15.0 - 16.0) Gray, CLAY; trace silt							

GROUNDWATER OBSERVATIONS

⊘ DURING DRILLING: 9'

☛ AT COMPLETION OF DRILLING: NR

⊘ AFTER NR HOURS: NR

NE - Not Encountered NR - Not Recorded

HOLE COLLAPSE

AT COMPLETION: NR

AFTER NR HOURS: NR

BACKFILL: Native Soils and/or Bentonite Chips

*LL = Liquid Limit - PI = Plasticity Index

*St = Hand Torvane Shear Strength

*Qp = Pocket Penetrometer

*Qu = Unconfined Compression Machine






















Project: Davison Road Landfill		Project Number: 1119.001		Client: Racer Trust		Boring No.: SB/MW-14-12		
Address, City, State: Davison Rd and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/17/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/17/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 10:20			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 12 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
0				Brown, Silt with fine grained Sand and Gravel, dry.	0.0		Protector/Concrete
2		100		Brown, Silt with Clay and Gravel, hard, dry.	0.0		Bentonite
4				S.A.A., dry.	0.0		Sand
6		100					
7	Standard Penetration Split Spoon Sampler (SPT)			Brown, fine grained Sand, trace Gravel, moist.	0.0		
8				Brown, fine grained Sand, trace medium grained Sand, wet.	0.0		
9				Brown, fine to medium grained Sand, wet.	0.0		
10		100					
12				S.A.A., wet.			
EOB							

Standard Penetration Split Spoon Sampler (SPT)	Soil Gas Sample Screen Interval
Direct Push Sampler	Stabilized Ground water
Water Sample	Groundwater At time of Drilling
HA Hand Auger	S.A.A Same As Above







Project: Davison Road Landfill		Project Number: 1119.001		Client: Racer Trust		Boring No.: SB/MW-1-12		
Address, City, State: Davison Rd and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/17/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/17/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 9:00			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 12 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		100		Brown, Silt with Sand and Gravel, dry.	0.0		Protector/Concrete
4				Brown Silt with Clay and Gravel, dry.	0.0		Bentonite
6		100		Brownish gray Silt, Clay and Sand with trace Gravel, moist.	0.0		Sand
8				Brown, Silt and fine grained Sand, moist.	0.0		
10		100					
12				Gray, Silt, wet.	0.0		
EOB							

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stabilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-2-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/16/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/16/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 12:53			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		90		Brown, Silty Sand, dry.	0.0		Protector/ Concrete
					0.0		Bentonite
4				S.A.A., very moist.	0.1		
6		85			0.0		
				Gray, Clay, moist.	0.0		
8					0.0		
10		50			0.0		
12				Gray, Silt, trace Clay, moist.	0.0		
14		70			0.0		
16				EOB	0.0		

 Standard Penetration Split Spoon Sampler (SPT)  Direct Push Sampler  Water Sample HA Hand Auger	 Soil Gas Sample Screen Interval  Stabilized Ground water  Groundwater At time of Drilling S.A.A. Same As Above
--	---







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-3-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/19/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/19/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 17:36			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		100		Dark Brown, fine to medium grained Sand and Silt, trace Organics, trace Gravel, dry.	0.0		Protector/Concrete
				Brown, Sandy Silt, some Organics, few Gravel, dry.	0.0		Bentonite
4				Gray, Silty Sand, fine to coarse grained, moist.			
6		80		S.A.A, wet.	0.0		
8				Gray, Silt, some Clay, wet.			
10		100			0.0		
12				Gray, Clayey Silt, wet.			
14		95			0.0		
16				EOB			

 Standard Penetration Split Spoon Sampler (SPT)  Direct Push Sampler  Water Sample HA Hand Auger	 Soil Gas Sample Screen Interval  Stabilized Ground water  Groundwater At time of Drilling S.A.A. Same As Above
--	---







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-4-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/19/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/19/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 11:33			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2	Standard Penetration Split Spoon Sampler (SPT)	90		Topsoil: Black, fine to medium grained Sand and Silt, some Organics, moist.	0.0		Protector/Concrete
				Brown, fine to medium grained Sand and Silt, moist.	0.0		Bentonite
4				Brown, fine to coarse grained Sand, few Cobbles, some Gravel, moist.	0.0		
6		90		Gray Silty Clay, wet.	0.0		
8				Gray, Clay, wet.	0.0		
10		85			0.0		
12				S.A.A, wet.	0.0		
14		80		Gray, Silty Clay, wet.	0.0		
16				EOB			

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stabilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-5-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/20/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/20/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 15:46			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
0.0				Concrete dust, some broken concrete, dry.	0.0		Protector/ Concrete
2.0		100		Foundry Sands, black fine to medium grained, trace Organics, trace metal pieces, moist.	0.0		
4.0				Black with reddish brown foundry Sand, fine to medium grained, moist.	0.0		Bentonite
6.0		100					
8.0				S.A.A, moist.	0.0		
10.0		100			0.0		Sand
12.0				Dark Gray, Clayey Silt, trace fine grained Sand, wet.	0.0		
13.0				Black, Sandy Silt, some Gravel and rocks, wet.	0.0		
14.0		60		Gray, Silt, trace Clay, wet.	0.0		2"x5"x#10 slot PVC well screen
16.0				EOB			

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-6-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/17/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/17/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 17:00			Backfilled: Sand & natural cuttings & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 15.5 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		100		Brown, Silt with Clay and Gravel, dry, hard.	0.0		Protector/ Concrete
4				Brown, Silt, trace Gravel, damp.	0.0		
6		100		S.A.A.	0.0		Natural Cuttings
10		100		Gray, Clay, moist.	0.0		Bentonite
14		75		Gray, fine to medium grained Sand, wet.	0.0		Sand
16				EOB, obstruction at 15.5'			2"x5"x#10 slot PVC well screen
17							

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stabilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-7-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/19/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/19/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 10:34			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		95		Black, fine grained Sand, some Organics, moist. Brown, fine grained Sand, some Silt, moist.	0.0 0.0		Protector/ Concrete
4				Brown, fine to medium grained Sand, some Silt, moist. Brown, Silt, trace Gravel, moist.	0.0		Bentonite
6		100		Brown, fine to medium grained Sand, very moist.	0.0		
8				Gray, Clay, moist.	0.0		
10		100		Brown, fine to medium grained Sand, wet.	0.0		
12				Gray, Clay, moist.	0.0		
14		95		Gray, Silt, wet.	0.0		
16				EOB			














 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-8-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/18/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/18/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 12:43			Backfilled: Sand, natural cuttings & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 15 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		95		Brownish orange, mottled, Sandy Silt, trace Gravel, moist.	0.0		Protector/Concrete
4				Brown, Sandy Silt, trace Gravel, dry.	0.0		Natural Cuttings
6	HA	100					Bentonite
8				Gray and pink, mottled, Silt, some Clay, moist.	0.0		
10		90		Gray, Silt, some Clay, wet.	0.0		
12				S.A.A, wet.	0.0		2"x5"x#10 slot PVC well screen
14		95					
16				EOB			













 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-9-12		
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/18/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/18/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 11:42			Backfilled: Sand, natural cuttings & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 15 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		90		Brownish orange, mottled, Sandy Silt, trace Organics, dry.	0.0		Protector/ Concrete
				Brown, fine grained Sand, some Silt, moist.	0.0		Natural Cuttings
4				Brown, Silt, some Clay, moist. S.A.A, trace Clay, moist.	0.0		Bentonite
6		100		Gray, Silt and Clay, moist.	0.0		Sand
8				Gray, Silt, some Clay, wet.	0.0		2"x5"x#10 slot PVC well screen
10		100		Wet.	0.0		
12				Gray, Silt, wet.	0.0		
14		100		Gray, fine to medium grained Sand, wet.	0.0		
16				EOB			

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1119.001		Client: Racer Trust		Boring No.: SB/MW-10-12		
Address, City, State: Davison Rd and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/18/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/18/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 10:48			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 12 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		90		Brown, Sand and Silt, some Organics, dry.	0.0		Protector/Concrete
				Brownish orange, mottled, Sandy Silt, moist.	0.0		
4				Wet.			
				Brown, Sandy Silt, moist.	0.0		
6		95		Wet.			2"x5"x#10 slot PVC well screen
				Gray, Sandy Silt, wet.	0.0		
8				Gray, Silt, some Clay, wet.	0.0		
		Gray, Silt, saturated.		0.0			
10		100					
12				EOB			

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-11-12	
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS	
Logged By: L. Lambert		Started: 7/19/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim		Completed: 7/19/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 16:50		Backfilled: Sand, natural cuttings & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
		Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		90		Brown, Silt and Sand, foundry fill, trace Organics, dry.	0.0		Protector/ Sand
				Brown and red, mottled, Silt and fine grained Sand, trace Organics, dry.	0.0		Bentonite
4				Brown and gray, mottled, Silt, dry.	0.0		
				Brown and orange, mottled, Silt and fine grained Sand, moist.	0.0		
6		100		Gray, Sandy Silt, trace Organics, moist.	0.0		Sand
8				Brown, Silty Sand, wet.	0.0		
				Gray, Clay, trace Silt, wet.	0.0		
10		85		S. A. A. with coarse grained Sand, wet.	0.0		2"x5"x#10 slot PVC well screen
12				Gray, Silt, some Clay, wet.	0.0		
14		80					
16				EOB			




 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stabilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above







Project: Davison Road Landfill		Project Number: 1125.001		Client: Racer Trust		Boring No.: SB/MW-12-12	
Address, City, State: Davison Road and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS	
Logged By: L. Lambert		Started: 7/17/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim		Completed: 7/17/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 13:00		Backfilled: Sand, natural cuttings & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
Groundwater Depth: N/A				Elevation: N/A		Total Depth of Boring: 16 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.			
2		75		Brown, Silt and Sand with concrete and Gravel, dry.	0.0		Protector/
4							
6		50					Bentonite
8				Brown, Silt and Clay, with Gravel, moist.	0.0		
10		50		Black, Clay with Silt and debris including rubber and Organics, moist.	0.0		
12				Gray, Silt and fine grained Sand, moist.	0.0		
				Gray, medium to coarse grained Sand, moist.	0.0		Sand
14		50		S.A.A., wet.	0.0		
16				Gray, Clay, moist.	0.0		2"x5"x#10 slot PVC well screen
				EOB			

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stablilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A. Same As Above

Project: Davison Road Landfill		Project Number: 1119.001		Client: Racer Trust		Boring No.: SB/MW-13-12		
Address, City, State: Davison Rd and Donegal, Burton, Michigan				Drilling Contractor: Wilcox		Drill Rig Type: Geoprobe AMS		
Logged By: L. Lambert		Date	Started: 7/17/2012		Bit Type: N/A		Hole Diameter: 4"	
Drill Crew: Ray/Jim			Completed: 7/17/2012		Hammer Type: N/A		Well Diameter: 2"	
Comments: sampled soil @ 11:30			Backfilled: Sand & bentonite chips		Hammer Weight: N/A		Hammer Drop: N/A	
			Groundwater Depth: N/A		Elevation: N/A		Total Depth of Boring: 12 feet	

Depth (feet)	Sample Type	% Recovery	Graphic Log	Lithology	PID	Well Construction	Well Construction Details			
				Soil Group Name: modifier, color, moisture, density/consistency, grain size, other descriptors Rock Description: modifier, color, hardness/degree of concentration, bedding and joint characteristics, solutions, void conditions.						
2		100		Brown, Silt and Sand, concrete, slag, dry.	0.2		Protector/Concrete			
									Bentonite	
4										
6										
				Brown, Silt, fine grained Sand and Clay with Gravel, dry.	0.0					
6				Brown, fine grained Sand, moist. Wet.	0.0					
8				Brown, Silt, wet.	0.0					
10										
12				Gray, Silt and Clay, plastic, moist.	0.0					
EOB										

 Standard Penetration Split Spoon Sampler (SPT)	 Soil Gas Sample Screen Interval
 Direct Push Sampler	 Stabilized Ground water
 Water Sample	 Groundwater At time of Drilling
HA Hand Auger	S.A.A Same As Above

BRI-85-PFS LAYER: ON=*, OFF=REF*
J: 2007\64448030\64448B12.dwg PENTABLE:PLT\FULL.CTB PRINTED:12/20/2007 8:24 AM BY: AFOX
PROJECTNAME: BBL IMAGES:
XREFS:




TABLE 1
GENERAL MOTORS CORPORATION

SITE INVESTIGATION REPORT
56-ACRE UNDEVELOPED PROPERTY ADJACENT TO DELPHI ENERGY
& ENGINE MANAGEMENT SYSTEMS, PLANT 600/700
SUMMARY OF SHALLOW SOIL BORING PHYSICAL CHARACTERISTICS - 2003

Location ID	Install Date	Coordinates		Ground Elevation	Survey Date	Boring Depth	Depth of Fill Material	Depth of Native Material
		X - Easting	Y - Northing					
FE-A1	12/8/2003	13321460.22	557221.36	762.20	1/4/2004	10.0	0-10	NA
FE-A2	12/8/2003	13321661.09	557229.95	762.33	1/4/2004	10.0	0-7.4	7.4-10.0
FE-A3	12/8/2003	13321559.24	557226.14	762.51	1/4/2004	10.0	0-6.5	6.5-10.0
FE-A4	12/8/2003	13321579.09	557224.56	762.48	1/4/2004	10.0	0-6.0	6.0-10.0
FE-A5	12/8/2003	13321613.41	557228.07	762.61	1/4/2004	10.0	0-6.0	6.0-10.0
FE-A6	12/9/2003	13321746.77	557233.95	762.93	1/4/2004	2.0	0-2.0	NA
FE-7	12/9/2003	13321896.65	557227.61	761.74	1/4/2004	3.0	0-3.0	NA
FE-A8	12/9/2003	13321685.97	557233.18	762.33	1/4/2004	4.0	0-4.0	NA
FE-B1	12/8/2003	13321573.92	557430.75	761.94	1/4/2004	5.0	0-5.0	NA
FE-B2	12/9/2003	13321743.63	557393.77	762.94	1/4/2004	5.0	0-2.0	2.0-5.0
FE-B3	12/9/2003	13321789.60	557384.07	763.30	1/4/2004	5.0	0-2.8	2.8-5.0
FE-B4	12/9/2003	13321840.82	557370.40	763.15	1/4/2004	4.0	0-1.7	1.7-4.0
FE-B5	12/9/2003	13321897.93	557352.48	762.80	1/4/2004	4.0	0-3.1	3.1-4.0
FE-C1	12/8/2003	13321570.91	557627.51	759.03	1/4/2004	10.0	NA	0-10.0
FE-C2	12/9/2003	13321644.29	557609.50	760.21	1/4/2004	5.0	NA	0-5.0
FE-C3	12/10/2003	13321514.80	557642.02	760.06	1/4/2004	5.0	NA	0-5.0
FE-D1	12/8/2003	13321570.75	557577.12	760.14	1/4/2004	10.0	NA	0-10.0
FE-D2	12/10/2003	13321507.88	557586.41	761.07	1/4/2004	5.0	NA	0-5.0
FE-D3	12/10/2003	13321459.83	557592.73	761.88	1/4/2004	5.0	0-2.5	2.5-5.0
FE-E1	12/8/2003	13321571.72	557477.78	762.15	1/4/2004	5.0	0-1.4	1.4-5.0
FE-F1	12/8/2003	13321570.52	557505.86	762.75	1/4/2004	1.0	0-1.0	NA
FE-F2	12/8/2003	13321620.63	557501.21	762.61	1/4/2004	5.0	0-2.3	2.3-5.0
FE-F3	12/8/2003	13321645.12	557496.39	762.28	1/4/2004	5.0	0-2.0	2.0-5.0
FE-F4	12/8/2003	13321668.85	557489.94	762.52	1/4/2004	5.0	0-2.1	2.1-5.0
FE-F5	12/9/2003	13321718.14	557474.30	762.72	1/4/2004	5.0	0-0.8	0.8-5.0
FE-F6	12/9/2003	13321742.12	557467.20	763.22	1/4/2004	5.0	0-1.5	1.5-5.0
FE-F7	12/9/2003	13321764.93	557458.34	763.29	1/4/2004	5.0	0-1.4	1.4-5.0
FE-F8	12/9/2003	13321883.48	557436.45	762.50	1/4/2004	5.0	0-0.3	0.3-5.0
FE-F9	12/9/2003	13321788.50	557451.93	763.37	1/4/2004	5.0	0-5.0	NA
FE-G1	12/9/2003	13321571.18	557539.90	761.52	1/4/2004	5.0	0-0.8	0.8-5.0
FE-G2	12/9/2003	13321751.86	557496.31	761.67	1/4/2004	5.0	0-1.0	1.0-5.0
FE-G3	12/9/2003	13321676.87	557516.62	761.78	1/4/2004	5.0	0-1.8	1.8-5.0
FE-G4	12/9/2003	13321625.80	557526.45	762.41	1/4/2004	5.0	0-2.4	2.4-5.0

**TABLE 1
GENERAL MOTORS CORPORATION**

**SITE INVESTIGATION REPORT
56-ACRE UNDEVELOPED PROPERTY ADJACENT TO DELPHI ENERGY
& ENGINE MANAGEMENT SYSTEMS, PLANT 600/700
SUMMARY OF SHALLOW SOIL BORING PHYSICAL CHARACTERISTICS - 2003**

Location ID	Install Date	Coordinates		Ground Elevation	Survey Date	Boring Depth	Depth of Fill Material	Depth of Native Material
		X - Easting	Y - Northing					
FE-H1	12/9/2003	13321660.92	557255.46	762.48	1/4/2004	5.0	0-1.0	1.0-5.0
FE-I1	12/9/2003	13321779.24	557426.72	763.25	1/4/2004	5.0	0-1.9	1.9-5.0
FE-I2	12/9/2003	13321866.06	557402.34	763.04	1/4/2004	5.0	0-1.2	1.2-5.0
FE-I3	12/9/2003	13321818.54	557418.96	763.06	1/4/2004	4.0	0-1.6	1.6-4.0
FE-J1	12/10/2003	13321522.66	557690.89	759.05	1/4/2004	0.5	0-4.0	4.0-5.0
FE-J2	12/10/2003	13321469.72	557699.78	759.87	1/4/2004	5.0	NA	0-5.0
FE-K1	12/10/2003	13321529.18	557733.09	758.61	1/4/2004	5.0	0-4.0	4-5.0
FE-K2	12/10/2003	13321480.48	557737.98	758.38	1/4/2004	5.0	0-4.0	4-5.0
FE-K3	12/10/2003	13321433.03	557741.87	759.78	1/4/2004	5.0	0-2.0	2.0-5.0
FE-K4	12/10/2003	13321321.82	557730.85	758.58	1/4/2004	5.0	0-2.5	2.5-5.0
FE-L1	12/10/2003	13321309.23	557778.22	756.74	1/4/2004	5.0	NA	0-5.0
FE-M1	12/10/2003	13321259.17	557929.72	758.56	1/4/2004	5.0	NA	0-5.0
FE-M2	12/10/2003	13321156.49	557960.55	760.78	1/4/2004	5.0	0-1.0	1.0-5.0
FE-M3	12/10/2003	13321069.93	558010.23	760.87	1/4/2004	5.0	0-5.0	NA
FE-N1	12/10/2003	13321307.78	558022.02	761.07	1/4/2004	5.0	0-3.0	3.0-5.0
FE-P1	12/10/2003	13321324.43	558121.23	762.38	1/4/2004	5.0	0-2.5	2.5-5.0
FE-P2	12/10/2003	13321413.47	558076.05	759.95	1/4/2004	5.0	0-5.0	NA
FE-P3	12/10/2003	13321369.30	558101.42	760.17	1/4/2004	5.0	0-0.3	0.3-5.0
FE-Q1	12/10/2003	13321344.52	558219.36	762.61	1/4/2004	5.0	0-2.5	2.5-5.0
FE-R1	12/10/2003	13321362.10	558317.08	763.50	1/4/2004	5.0	NA	0-5.0
FE-R2	12/10/2003	13321263.71	558340.20	761.93	1/4/2004	5.0	NA	0-5.0
FE-R3	12/10/2003	13321198.71	558345.66	761.07	1/4/2004	5.0	0-1.5	1.5-5.0
FE-S1	12/10/2003	13321376.78	558605.99	759.85	1/4/2004	5.0	0-5.0	NA
FE-S2	12/10/2003	13321169.31	558588.46	761.07	1/4/2004	5.0	0-5.0	NA
FE-T1	12/10/2003	13321311.54	558706.08	759.97	1/4/2004	5.0	0-3.0	3.0-5.0
FE-T2	12/10/2003	13321377.99	558707.81	758.83	1/4/2004	5.0	NA	0-5.0
FE-U1	12/10/2003	13321313.01	558796.42	757.92	1/4/2004	5.0	NA	0-5.0
FE-U4	12/10/2003	13320716.58	558824.75	755.35	1/4/2004	5.0	NA	0-5.0

Notes:

1. Elevations are based on North American Vertical Datum of 1988.
2. Coordinates are based on North American Datum 1983, Michigan, South Zone.
3. Depths are in feet below ground surface.


TABLE 3
GENERAL MOTORS CORPORATION

SITE INVESTIGATION REPORT
56-ACRE UNDEVELOPED PROPERTY ADJACENT TO DELPHI ENERGY
& ENGINE MANAGEMENT SYSTEMS, PLANT 600/700
SUMMARY OF LITHOLOGIC DESCRIPTIONS AND PID READINGS - 2003/2004/2007

Location	Depth (ft bgs)	Lithologic Description	PID Readings
FA-1	0-2	Black SAND some SILT	0.5
FA-2	0-2	Black and tan SAND	0.3
FA-3	0-2	Brown SAND, SILT, and CLAY	0.7
FA-4	0-2	Black SAND and SILT with CLAY	0.7
FA-5	0-2	Dark brown SAND and SILT with CLAY	0.3
FA-6	0-2	Brown SILT and CLAY	0.5
FA-7	0-2	Dark brown SAND and SILT	0.4
FA-8	0-2	Dark brown SAND and SILT	0.2
FA-9	0-2	Dark brown SILT and CLAY	0.7
FA-10	0-2	Dark brown SAND, SILT and CLAY	0.8
FA-11	0-2	Dark brown SAND and SILT with CLAY	0.3
FA-12	0-2	Dark brown SAND and SILT	0.4
FA-13	0-2	Brown SAND and SILT	0.2
FA-14	0-2	Dark brown SAND and SILT with CLAY	0.3
FA-15	0-2	Dark brown SAND and SILT	0.2
FA-16	0-2	Tan to brown CLAY	0.9
FA-17	0-2	Dark brown SAND and SILT	1.9
SB-1	0-10	Brown SILT over dark gray CLAY	0.0
SB-2	0-10	Brown SILT over brown SAND and gray CLAY	0.0
SB-3	0-10	Brown SILT over brown SAND	0.0
SB-4	0-10	Brown SILT over brown SAND	0.0
SB-5	0-10	Brown SILT over brown SAND and gray CLAY	0.0
SB-6	0-6	Brown SILT	0.0
SB-7	0-10	Brown SILT over brown SAND and gray CLAY	0.0
SB-8	0-10	Brown SILT over brown SAND	0.0
SB-9	0-2	Brown SILT	0.0
SB-10	0-2	Brown SILT	0.0


Notes:

1. Lithologic descriptions and PID readings from FA borings recorded during sampling 3/3/04. SB borings recorded during sampling on 8/8/07.
2. ft bgs = feet below ground surface.



Legend

---	Property Boundary
-*-*-	Fence
⊕	Observation Well
⊗	Soil Boring



 North
 0 ————— 600'
 APPROX. SCALE

DELPHI
Energy & Engine Management Systems

TECHNA CORPORATION
44808 Helm Street
Plymouth, MI 48170-6028
(313) 454-1100

Figure 3
Observation Well/Soil Boring Locations
 Delphi Energy & Engine Management Systems - Flint East
 Flint, Michigan

TPN: 654-01M
 Date: 5-6-88
 Rev.
 Drn: 000
 Ref:
 File: 65401M-2.DWG



Datum: Referenced to
NGVD at MW1 and MW3

0 300'

HORIZONTAL SCALE

Vertical Exaggeration = 50x

LEGEND

Potential
Measurements (03/15/96)

FILL

SAND

SILT

SILT and SAND

CLAY

Screened Interval



DELPHI
Energy & Engine Management Systems

IPN: 00636-01X
Date: 4-17-96
Per: 060
Dm: 65401M-4.DEC
Rel: 114
TUA: 434-1100

TECHNA
CORPORATION
44808 Main Street
Plymouth, MI 48170
(313) 434-1100

Figure 4
Geologic Cross-Section
(W-E)

Delphi Energy & Engine Management Systems
- Flint East, Flint, Michigan



0 600'
APPROX. SCALE

DELPHI
Energy & Engine Management Systems

Figure 5
Groundwater Potentiometric Measurements (03/15/96)
Delphi Energy & Engine Management Systems - Flint East
Flint, Michigan

TPN: 654-01M
Date: 6-6-96
Rev. 080
Dwn:
Rft:
File: 65401M-3.DWG

TECHNA
CORPORATION

44808 Helm Street
Plymouth, MI 48170-6026
(313) 454-1100

Techna Corporation
Plymouth, Michigan

Log of Boring B5

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-01M-002

SURFACE ELEVATION:

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL:

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger

STATIC H2O ELEV.:

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 15 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
3	B5-A 3-5'	1 3 3 5	<1			CL	CLAY: soft to medium stiff, moist, yellow brown.	Scattered gravels and construction debris noted on ground surface.
6						SM	SAND: some silt, fine to medium, loose, moist, yellow brown.	
9	B5-B 8-10'	3 3 6 10	<1			CL	CLAY: trace fine sand, silts and fine gravels, stiff, moist, yellow brown.	
15	B5-C 13-15'	2 3 4 5	<1			CL	CLAY: trace fine gravels, stiff, moist, gray.	
15							END OF BORING	
18								
21								

Techna Corporation
Plymouth, Michigan

Log of Boring B6

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-01M-002

SURFACE ELEVATION:

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL: 13 Feet

DRILLING METHOD: 4.5-Inch ID Hollow Stem Auger





STATIC H2O ELEV.:

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 15 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO.	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
			0	50				
3	B6-A 3-5'	5 8 7 9	<1			CL	CLAY: some silts, trace fine sands, stiff, damp to moist, yellow brown.	Terminated B6 at 15' because no fill was encountered. Note off-set boring was located to west at B11.
6						SM	SAND: some silt, fine, loose, moist, yellow brown.	
9	B5-B 8-10'	3 4 3 5	<1			CL	CLAY: medium stiff, moist, gray.	
12								
15	B6-C 13-15'	2 3 3 3	<1			ML	SILT: trace clay, soft, with occasional very thin beds of clay, moist to saturated, gray.	
							END OF BORING	
18								
21								

Techna Corporation
Plymouth, Michigan

Log of Boring B7

PROJECT: *GM Corporation*

LOCATION: *Green Parcel East of Delphi Plant 700*

PROJECT NO.: *00654-01M-002*

SURFACE ELEVATION:

DATE START/FINISH: *3-11-96*

INITIAL H2O LEVEL: *8 Feet*

DRILLING METHOD: *4.5-inch ID Hollow Stem Auger*



STATIC H2O ELEV.:

SAMPLING METHOD: *2 foot by 2-inch Split Barrel Sampler*

TOTAL DEPTH: *10 Feet*

DRILLING COMPANY: *Carlo Environmental*

LOGGED BY: *(074)*

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
			0	50				
3	B7-A 3-5'	5 8 12 10	<1			SM	SAND: trace silt, fine, medium dense, moist, yellow brown.	Terminated B7 at 10' because no fill was encountered. Note off-set boring was located to south at B10. Scattered gravels noted on ground surface.
6								
9	B7-B 8-10'	3 2 5 2	<1			ML	Saturated at 8 feet. SILT: some clay, soft, saturated, gray.	
12							END OF BORING	
15								
18								
21								

Techna Corporation
Plymouth, Michigan

Log of Boring B8

PROJECT: *GM Corporation*

LOCATION: *Green Parcel East of Delphi Plant 700*

PROJECT NO.: *00654-OIM-002*

SURFACE ELEVATION:

DATE START/FINISH: *3-11-96*

INITIAL H2O LEVEL:

DRILLING METHOD: *4.5-inch ID Hollow Stem Auger*

STATIC H2O ELEV.:

SAMPLING METHOD: *2 foot by 2-inch Split Barrel Sampler*

TOTAL DEPTH: *20 Feet*

DRILLING COMPANY: *Carlo Environmental*

LOGGED BY: *(074)*

DEPTH feet	LAB SAMPLE NO.	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
			0	50				
3	B8-A 3-5'	2 2 3 4	<1		GP SP	SC	Fill gravel and sand.	
6								
9	B8-B 8-10'	2 2 4 5	<1				Fill Sand and Clay, fine sand, loose sand, soft clay, moist, brown black sand in thin beds throughout sample.	
12								
15	B8-C 13-15'	1 1 1 1	<1			CL	Fill Sand, fine, moist, black (apparent foundry sand).	
18	B8-D 18-20'	6 12 16 18	<1			SM ML	CLAY: trace silt, medium stiff, moist, black gray.	
21							Sand with silt, fine, very loose, saturated, gray at 14'5" to 14'8", coarse sand with organics, black gray to gray.	
							SILT: some fine sand, dense, saturated, gray.	
							END OF BORING	

Techna Corporation
Plymouth, Michigan

Log of Boring B9

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-OIM-002

SURFACE ELEVATION:

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL: 6 Feet

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger




STATIC H2O ELEV.:

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 15 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
3	B9-A 3-5'	3 3 3 5	<1			CL	CLAY: trace of fine sand and gravel, medium stiff to stiff, moist, yellow brown.	
6								
9	B9-B 6-10'	3 8 8 10	<1			SM ML	SAND and SILT: fine sands, loose to medium dense, saturated, yellow brown.	
12								
15	B9-C 13-15'	2 5 8 8	<1			ML	SILT: some clay, trace fine sands, stiff, saturated, gray.	
18								
21							END OF BORING	

Techna Corporation
Plymouth, Michigan

Log of Boring B10

PROJECT: *GM Corporation*

LOCATION: *Green Parcel East of Delphi Plant 700*

PROJECT NO.: *00654-01M-002*

SURFACE ELEVATION:

DATE START/FINISH: *3-11-96*

INITIAL H2O LEVEL: *8 Feet*

DRILLING METHOD: *4.5-inch ID Hollow Stem Auger*






STATIC H2O ELEV.:

SAMPLING METHOD: *2 foot by 2-inch Split Barrel Sampler*

TOTAL DEPTH: *15 Feet*

DRILLING COMPANY: *Carlo Environmental*

LOGGED BY: *(074)*

DEPTH feet	LAB SAMPLE NO.	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
			0	50				
3	B10-A 3-5'	3 4 6 2	<1			SP	Gravels and Sand: base coarse.	B10 located in center of gravel road, off-set to south from B7.
6						SM	SAND: trace silt, fine, loose, moist, yellow brown.	
9	B10-B 8-10'	3 4 6 7	<1				Saturated at 8 feet. Silt in thin lamina throughout sample.	
12								
15	B10-C 13-15'	3 5 4 3	<1			CL	CLAY: trace fine gravel, medium stiff, moist, gray.	
18							END OF BORING	
21								

Techna Corporation
Plymouth, Michigan

Log of Boring B11

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-01M-002

SURFACE ELEVATION:

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL:

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger





STATIC H2O ELEV.:

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 10 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	REMARKS
			VALUES	PROFILE				
	B11-A 0-2'	N/A	<1			SM	Fill SAND: little silt, fine, damp, yellow brown.	B11 off-set to west from B6.
						SP	Fill SAND: fine, moist, red brown (apparent foundry sand).	
3	B11-B 3-5'	2 4 4 5	<1			CL	CLAY: some fine sand, medium stiff to stiff, moist, yellow brown.	
9	B11-C 8-10'	4 6 8 10	<1					
							Gray color change noted at 10 feet. END OF BORING	
12								
15								
18								
21								

Techna Corporation
Plymouth, Michigan

Log of Monitoring Well MW1

PROJECT: GM Corporation

PROJECT NO.: 00654-01M-002

DATE START/FINISH: 3-11-96

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

DRILLING COMPANY: Carlo Environmental

LOCATION: Green Parcel East of Delphi Plant 700

SURFACE ELEVATION: 760.84 Feet

INITIAL H2O LEVEL: 11 Feet

STATIC H2O ELEV.: 754.80 Feet (03/15/96)

TOTAL DEPTH: 20 Feet

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO.	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	WELL DIAGRAM
			VALUES	PROFILE				
			0	50				
3	MW1-A 3-5'	3 3 6 7	<1		CL	CL	Fill Clay, some fine sand, damp, yellow brown.	<p>2" inch dia. PVC Riser</p> <p>Concrete</p> <p>Bentonite Chips</p> <p>Filter Sand</p> <p>2 inch dia. PVC Screen (0.010-slot)</p>
6					SP	SP	Fill Sand, fine, loose to medium dense, damp, black, apparent foundry sand, red brick in sample.	
9	MW1-B 8-10'	8 8 10 7	<1		SP	SP	Fill Sand, fine, loose to medium dense, traces of silt, very moist, yellow brown, apparent foundry sand.	
12							Saturated at 11 feet.	
15	MW1-C 13-15'	2 5 9 7	<1		SM ML	SM ML	SILT: some fine sand, with occasional very thin beds of clay, medium stiff, saturated, gray.	
18	MW1-D 18-20'	1 2 2 2	<1		CL	CL	CLAY: little silt, very soft to soft, moist, gray	<p>2" inch dia. PVC Riser</p> <p>Concrete</p> <p>Bentonite Chips</p> <p>Filter Sand</p> <p>2 inch dia. PVC Screen (0.010-slot)</p>
21							END OF BORING	

Techna Corporation
Plymouth, Michigan

Log of Monitoring Well MW2

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-OIM-002

SURFACE ELEVATION: 764.23 Feet

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL: 11 Feet

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger

STATIC H2O ELEV.: 754.22 Feet (03/15/96)

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 20 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	WELL DIAGRAM
			VALUES	PROFILE				
3	MW2-A 3-5'	10 10 9 11	<1		SP	SP	Fill Sand, some gravels, (apparent slag material) yellow brown, black, red brown.	<p>2" inch dia. PVC Riser</p> <p>Concrete</p> <p>Bentonite Chips</p> <p>Filter Sand</p> <p>2" inch dia. PVC Screen (0.010-slot)</p>
6								
9		42 24 11 5					No sample return, driving concrete in split barrel sampler. Drilled through concrete from 8-10'.	
12								
15	MW2-B 14-16'	2 2 2 2 2 1 1	<1		ML SM	ML SM	SILT and SAND: fine to medium, trace fine gravels, wood debris, saturated, gray. No sample return from 13 to 15 feet.	<p>2" inch dia. PVC Riser</p> <p>Concrete</p> <p>Bentonite Chips</p> <p>Filter Sand</p> <p>2" inch dia. PVC Screen (0.010-slot)</p>
18	MW2-C 18-20'	1 3 4 2	<1		CL	CL	CLAY: trace silt, and fine gravels, soft to medium stiff, moist, gray.	
21							END OF BORING	

Techna Corporation
Plymouth, Michigan

Log of Monitoring Well MW3

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-OIM-002

SURFACE ELEVATION: 767.10 Feet

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL: 9 Feet

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger

STATIC H2O ELEV.: 766.04 Feet (03/15/96)

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 15 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	WELL DIAGRAM
			VALUES	PROFILE				
3	MW3-A 3-5'	4 8 8 11	<1			CL	CLAY: trace silt and fine sand, stiff to very stiff, moist, yellow brown.	
6								
9	MW3-B 8-10'	3 8 11 12	<1			SM ML	SAND and SILT: fine, medium dense, saturated, yellow brown.	
12								
15	MW3-C 13-15'	2 5 5 10	<1			CL	CLAY and SILT: clay and silt thin beds throughout sample, very moist, gray.	
18								
21							END OF BORING	

Techna Corporation
Plymouth, Michigan

Log of Monitoring Well MW4

PROJECT: GM Corporation

LOCATION: Green Parcel East of Delphi Plant 700

PROJECT NO.: 00654-01M-002

SURFACE ELEVATION: 763.65 Feet

DATE START/FINISH: 3-11-96

INITIAL H2O LEVEL:

DRILLING METHOD: 4.5-inch ID Hollow Stem Auger

STATIC H2O ELEV.: 759.27 Feet (03/15/96)

SAMPLING METHOD: 2 foot by 2-inch Split Barrel Sampler

TOTAL DEPTH: 15 Feet

DRILLING COMPANY: Carlo Environmental

LOGGED BY: (074)

DEPTH feet	LAB SAMPLE NO.	BLOWS/0.5 ft.	PID (relative ppm)		GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION	WELL DIAGRAM
			VALUES	PROFILE				
3			0	50		CL	CLAY: some fine sand, moist, yellow brown.	
6								
9								
12						SM	SAND: some silt, fine, saturated, gray brown to gray.	
15							END OF BORING Note: Soil profile logged from soil cuttings and drilling rate changes.	
18								
21								